



МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

## Cisco Catalyst 9200L 24-port PoE+ 4x1G uplink Switch, Network Advantage



Модел : C9200L-24P-4G-A

Cisco Catalyst 9200L 24-port PoE+ 4x1G uplink Switch, Network Advantage

Суич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 24x10/100/1000Base-T

Power Over Ethernet (PoE): IEEE 802.3at PoE+ (up to 30W per port), Perpetual PoE, Fast PoE; Available PoE Power:

370W\* (Default primary power supply - PWR-C5-600WAC),

740W\* (Optional secondary power supply -

PWR-C5-600WAC), \*Limited by port number and port rating

Uplink портове: 4x10/100/1000Base-T

Свободни (10GB) слотове: No

Управление: SNMPv1, SNMPv2c, and SNMPv3; RMON I and II standards; Internet Group Management Protocol (IGMP);

CLI; TCP; UDP

Stackable: Cisco StackWise-80 stacking ports: copper-based

Cisco StackWise cabling, Stacking hardware

(C9200L-STACK-KIT=), Supported stack members: Other

C9200L models with same license level (8 Number of members)

Fans: Fixed redundant

Захранване: Dual field-replaceable power supplies, Default primary AC power supply: PWR-C5-600WAC

Routing: Layer 3 Advanced

Памет (Flash, RAM): Flash memory: 4 GB; RAM: 2 GB DRAM

Капацитет за маршрутизиране/превключване, Gbps: 56 Gbps

Пропускателна способност, Mpps: 83.33 Mpps

MAC адреси: 16000 MAC address

VLAN (брой, стандарти): VLAN IDs: 1024; IEEE 802.1Q

VLAN

QoS: Granular wireless bandwidth management and fair sharing, 802.1p Class of Service (CoS) and Differentiated Services Code Point (DSCP) field classification, Shaped Round Robin (SRR) scheduling, Committed Information Rate (CIR), and eight egress queues per port

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3bz, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.1x-Rev, IEEE 802.3x

L3 мрежови стандарти: Advanced IP unicast routing protocols: full OSPF, EIGRP, IS-ISv4  
IPv6 functionality: IPv6 routing (using OSPFv3 and EIGRPv6) is supported in hardware for maximum performance; IPv6 addressing is supported on interfaces with appropriate show commands for monitoring and troubleshooting  
Сигурност: Enhanced security with AES-128 MACsec encryption, policy-based segmentation, and trustworthy systems  
Размери (Ш, Д, В), mm: 445 x 288 x 44  
Опция за монтаж: Rackmount  
Други: Необходим е минимум 3-годишен лиценз DNA Advantage.

Цена : 5436.26 лв. с ДДС

*Наличност: Този продукт е бил добавен в нашия каталог на Ср 17 януари, 2024*