

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Dell Networking S3124F, L3, 24x 1GbE SFP, 2xCombo, 2x 10GbE SFP+ fixed ports, Stacking, IO to PSU air, 1x AC PSU, 3Y PS NBD, STOCK Smart Value, 210-AIMS



Модел : DNS3124F

Dell Networking S3124F, L3, 24x 1GbE SFP, 2xCombo, 2x 10GbE SFP+ fixed ports, Stacking, IO to PSU air, 1x AC PSU, 3Y PS NBD, STOCK Smart Value, 210-AIMS

Суич, тип: Fixed Port

Общ брой портове: 24

Основни портове, тип: 24x 1GbE SFP

Power Over Ethernet (PoE): No

Uplink портове: 2x 10GbE SFP

Свободни (10GB) слотове: Hot swappable expansion module supporting dual-port SFP+ or dual-port 10GBaseT

Управление: Management via an intuitive and familiar CLI, SNMP-based management console application (including Dell OpenManage Network Manager), Telnet or serial connection

Stackable: Yes

Fans: Redundant variable speed fans

Захранване: 1x 200W PSU included

Routing: Layer 3 Advanced

Памет (Flash, RAM): Flash memory: 1G

Капацитет за маршрутизиране/превключване, Gbps: 212 Gbps

Пропускателна способност, Mpps: 158 Mpps

MAC адреси: 56K (80K in L2 scaled mode)

VLAN (брой, стандарти): 802.1Q VLAN Tagging, Double VLAN Tagging, GVRP, 802.3ac Frame Extensions for VLAN Tagging

QoS: 8 priority queues per port

L2 мрежови стандарти: IEEE compliance: 802.1AB, 802.1D, 802.1p, 802.1Q, 802.1Qbb, 802.1Qaz, 802.1s, 802.1w, 802.1x, 802.1x-2010, 802.3ab, 802.3ac, 802.3ad, 802.1ax, 802.3ae, 802.3af, 802.3at, 802.3az, 802.3u, 802.3x, 802.3z

IPv6 functionality: All protocols, including IPv4 and IPv6

Сигурност: TACACS+ accounting and RADIUS support,

Размери (Ш, Д, В), mm: 407 x 434 x 44

Опция за монтаж: Rackmount

Други: 1x RJ45 console/management port with RS232 signaling (RJ-45 to female DB-9 connector cable included), Out-of-band management port (10/100/1000BASE-T) USB (Type A) port for configuration via USB flash drive



Цена : 9364.22 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пт 14 юни, 2024