

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Dell Networking S3148, L3, 48x 1GbE, 2xCombo, 2x 10GbE SFP+ fixed ports, Stacking, IO to PSU airflow, 1x AC PSU, LLW 210-AIMR



Модел : DNS3148T

Dell Networking S3148, L3, 48x 1GbE, 2xCombo, 2x 10GbE SFP+ fixed ports, Stacking, IO to PSU airflow, 1x AC PSU, LLW 210-AIMR

Суич, тип: Fixed Port

Общ брой портове: 48

Основни портове, тип: 48 x 1GbE SFP

Power Over Ethernet (PoE): No

Uplink портове: 2-port 10 Gigabit BASE-T RJ45 hot

swappable uplink module: option available 2-port 10 Gigabit

SFP+ hot swappable uplink module:

Свободни (10GB) слотове: Hot swappable expansion module supporting dual-port SFP+ or dual-port 10GBaseT

Управление: Management via an intuitive and familiar CLI, SNMP-based management console application (including Dell OpenManage Network Manager), Telnet or serial connection

Stackable: Yes

Fans: Redundant variable speed fans

Захранване: 1x 200 W PSU included

Routing: Layer 3 Advanced

Памет (Flash, RAM): 256 MB

Капацитет за маршрутизиране/превключване, Gbps: 260 Gbps

Пропускателна способност, Mpps: 193 Mpps

MAC адреси: 56K (80K in L2 scaled mode)

VLAN (брой, стандарти): 802.1Q VLAN Tagging, Double VLAN Tagging, GVRP, 802.3ac Frame Extensions for VLAN Tagging

QoS: 8 priority queues per port

L2 мрежови стандарти: IEEE compliance: 802.1AB, 802.1D, 802.1p, 802.1Q, 802.1Qbb, 802.1Qaz, 802.1s, 802.1w, 802.1x, 802.1x-2010, 802.3ab, 802.3ac, 802.3ad, 802.1ax, 802.3ae, 802.3af, 802.3at, 802.3az, 802.3u, 802.3x, 802.3z

IPv6 functionality: All protocols, including IPv4 and IPv6

Сигурност: TACACS+ accounting and RADIUS support,

Размери (Ш, Д, В), mm: 407 x 434 x 44

Опция за монтаж: Rackmount

Други: 1x RJ45 console/management port with RS232 signaling (RJ-45 to female DB-9 connector cable included), Out-of-band management port (10/100/1000BASE-T) USB



(Type A) port for configuration via USB flash drive

Цена : 9833.60 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пн 01 юли, 2024