

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Cisco CBS250 Smart 24-port GE, Partial PoE, 4x1G SFP



Модел : CBS250-24PP-4G-EU

Cisco CBS250 Smart 24-port GE, Partial PoE, 4x1G SFP

Суич, тип: Fixed Port

Общ брой портове: 24

Основни портове, тип: RJ-45 10/100/1000 Mbps

Power Over Ethernet (PoE): PoE+ (100W)

Uplink портове: 4x 1G SFP

Свободни (10GB) слотове: -

Управление: On-device UI and Cisco Business Dashboard

Stackable: -

Fans: Fanless

Захранване: Internal (100 to 240V 50 to 60 Hz)

Routing: Layer 3 static routing (IPv4 routing - Wire-speed routing of IPv4 packets. Up to 32 static routes and up to 16 IP interfaces; IPv6 routing - Wire-speed routing of IPv6 packets)

Памет (Flash, RAM): Flash: 256 MB; CPU memory: 512 MB, Packet buffer: 1.5 MB

Капацитет за маршрутизиране/превключване, Gbps: 56 Gbps

Пропускателна способност, Mpps: 41.66 Mpps

MAC адреси: 8K addresses

VLAN (брой, стандарти): Support for up to 255 active VLANs simultaneously; Port-based and 802.1Q tag-based VLANs; Management VLAN; Guest VLAN; Voice VLAN; Generic VLAN Registration Protocol (GVRP) and Generic Attribute Registration Protocol (GARP); IEEE 802.1Q/p VLAN QoS: Priority levels: 8 hardware queues; Scheduling, Class of service Port based; 802.1p VLAN priority based; IPv4/v6 IP precedence/Type of Service (ToS)/DSCP based; Differentiated Services (DiffServ); classification and re-marking ACLs, trusted QoS

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3z, IEEE 802.3x Flow Control, IEEE 802.3 ad LACP, IEEE 802.1D (STP), IEEE 802.1Q/p VLAN, IEEE 802.1w RSTP, IEEE 802.1s Multiple STP, IEEE 802.1X, IEEE 802.3af, IEEE 802.3at, RFC

IPv6 functionality: IPv6 host mode, IPv6 over Ethernet, Dual IPv6/IPv4 stack, IPv6 Neighbor Discovery (ND), IPv6 stateless address auto configuration, Path (MTU discovery, Duplicate Address Detection (DAD), ICMP, USGv6, IPv6 over IPv4 network with ISATAP

Сигурност: SSL; SSH; IEEE 802.1X (authenticator role) -

RADIUS) authentication, guest VLAN, single/multiple host mode, and single/multiple sessions; STP; SCT; SSD; Trustworthy systems; Port security; Storm control; DoS prevention; ACLs
Размери (Ш, Д, В), mm: 445 x 299 x 44 mm
Опция за монтаж: Rackmount
Други: Spanning Tree Protocol (STP), access control list (ACL)

Цена : 801.47 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 03 октомври, 2024