

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

ZyXEL GS1900-48HP v2, 48-port GbE L2 Smart Switch, 170 Watt, rackmount



Модел : GS190048HPV2-EU0101F

ZyXEL GS1900-48HP v2, 48-port GbE L2 Smart Switch, 170 Watt, rackmount

Суич, тип: Fixed Port

Общ брой портове: 50

Основни портове, тип: 48x10/100/1000Base-T

Power Over Ethernet (PoE): PoE+ (170W)

Uplink портове: 2xSFP

Свободни (10GB) слотове: No

Управление: Built-in Web-based browser for simple configuration and management; Network Management: SNMP v1, v2, v3; RMON (1, 2, 3, 9); ICMP echo/echo reply; Syslog; IEEE 802.1AB LLDP; IEEE 802.1AB LLDP-MED
Stackable: No

Fans: Yes

Захранване: External (100 - 240 V AC, 50/60 Hz)

Routing: Layer 2 Only

Памет (Flash, RAM): Packet Buffer: 525 K

Капацитет за маршрутизиране/превключване, Gbps: 100 Gbps

Пропускателна способност, Mpps: 74 Mpps

MAC адреси: 8000 MAC address table size

VLAN (брой, стандарти): Port-based VLAN, IEEE 802.1Q

VLAN tagging, IEEE 802.3ad LACP, Guest VLAN, Voice VLAN

QoS: IEEE 802.1p priority queues per port, IEEE 802.1p Queuing method (scheduler), Input priority mapping, Rate limiting per port (ingress/egress)

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x flow control, IEEE 802.3az EEE support, IEEE 802.1p CoS support, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s

L3 мрежови стандарти: -

IPv6 functionality: IPv6 over Ethernet, Dual-stack, ICMPv6, Neighbor discovery, Auto configuration, Static IPv6 address and prefix length, Static IPv6 default gateway, IPv6 duplicate address detection

Сигурност: IEEE 802.1x, Port security, Layer 2 MAC filtering, Static MAC forwarding, RADIUS, TACACS+, SSL, Management VLAN, CPU defense engine, DoS prevention

Размери (Ш, Д, В), mm: 441 x 270 x 44

Опция за монтаж: Rackmount

Други: IGMP snooping (v1, v2, v3)



Цена : 960.55 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пн 29 януари, 2024

November 14, 2024, 6:18 a.m.