

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

ASUS PRIME B550-PLUS



Модел : ASUS PRIME B550-PLUS /AM4

ASUS PRIME B550-PLUS

Graphics: 1 x DisplayPort 1.2 *; 1 x HDMI 2.1(4K@60HZ)

CPU's supported: Build in AMD AM4 Socket 3rd Gen AMD Ryzen™ Processors *

Chipset: AMD B550

Expansion Slots: 3rd Gen AMD Ryzen™ Processors: 1 x PCIe 4.0 x16 (x16 mode); AMD B550 Chipset: 1 x PCIe 3.0 x16 (x4 mode); 3 x PCIe 3.0 x1 *1

Storage: Total supports 2 x M.2 slots and 6 x SATA 6Gb/s ports; 3rd Gen AMD Ryzen™ Processors : 1 x M.2

Socket 3, with M key, type 2242/2260/2280/22110 storage devices support(SATA & PCIE 4.0 x4 mode); AMD B550 Chipset : 1 x M.2 Socket 3, with M key, type

2242/2260/2280/22110 storage devices support (SATA & PCIE 3.0 x 4 mode)*2; 6 x SATA 6Gb/s port(s), *2; Support Raid 0, 1, 10

Memory type: 4 x DIMM, Max. 128GB, DDR4

4600(O.C.)/4400(O.C.)/4266(O.C.)/4133(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.)/3600(O.C.)/3466(O.C.)/3333(O.C.)/3200/3000/2800/2666/2400/2133 MHz ECC and non-ECC,

Un-buffered Memory * Next Generation AMD Ryzen PRO Processors; 4 x DIMM, Max. 128GB, DDR4

4800(O.C.)/4600(O.C.)/4466(O.C.)/4400(O.C.)/4266(O.C.)/4133(O.C.)/4000(O.C.)/3866(O.C.)/3600(O.C.)/3466(O.C.)/3200/3000/2800/2666/2400/2133 MHz ECC and non-ECC,

Un-buffered Memory Dual Channel Memory Architecture

I/O: 1 x DisplayPort; 1 x HDMI; 1 x LAN (RJ45) port(s); 2 x USB 3.2 Gen 2 (teal blue) (1 x Type-A+1 x USB

Type-C®); 4 x USB 3.2 Gen 1 (blue) Type-A; 2 x USB 2.0; 1 x Optical S/PDIF out; 5 x Audio jack(s)

Connectors: 1 x CPU Fan connector(s); 1 x CPU OPT Fan connector(s); 3 x Chassis Fan connector(s); 1 x AIO_PUMP connector;

2 x Aura RGB Strip Headers; 1 x Addressable Gen 2 header(s); 1 x USB 3.2 Gen 1(up to 5Gbps) connector(s)

support(s) additional 2 USB 3.2 Gen 1 port(s); 2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 port(s); 1 x M.2

Socket 3 with M key, type 2242/2260/2280/22110 storage devices support(SATA & PCIE 4.0 x4 mode); 1 x M.2

Socket 3 with M key, type 2242/2260/2280/22110 storage devices support (SATA & PCIE 3.0 x 4 mode); 1 x SPI TPM header; 6 x SATA 6Gb/s connector(s); 1 x Thunderbolt

header(s); 1 x 24-pin EATX Power connector(s); 1 x 8-pin

EATX 12V Power connectors; 1 x Front panel audio connector(s) (AAFP); 1 x Thermal sensor connector(s); 1 x Clear CMOS jumper(s); 1 x System panel connector; 1 x COM port header

Audio: Realtek ALC887 7.1-Channel High Definition Audio CODEC; - Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking, up to 24-Bit/192kHz playback; Audio Feature : - Optical S/PDIF out port(s) at back panel; - LED-illuminated design; - Audio Shielding; - Dedicated audio PCB layers; - Premium Japanese audio capacitors; - Unique de-pop circuit

LAN: Realtek® RTL8111H; ASUS LANGuard

BIOS: 256 Mb Flash ROM, UEFI AMI BIOS

Form Factor: ATX Form Factor; 12 inch x 9.6 inch (30.5 cm x 24.4 cm)

OS: Windows®; 10 64-bit

Warranty: 36 Months

Цена : 231.28 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Сб 06 април, 2024