

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

ASUS ROG STRIX B450-F GAMIN II



Модел : ASUS ROG STRIX B450-F GAMIN II

ASUS ROG STRIX B450-F GAMIN II

Graphics: 1 x HDMI 2.0b; 1 x DisplayPort 1.2

CPU's supported: AMD AM4 Socket for AMD Ryzen™

5000 Series/ 4000 G-Series/ 3rd/2nd/1st Gen AMD

Ryzen™/ 2nd and 1st Gen AMD Ryzen™ with

Radeon™ Vega Graphics/ Athlon™ with

Radeon™ Vega Graphics Processors Processors;

Chipset: AMD B450

Expansion Slots: 2 x PCIe 3.0 x16 (x16 or x8/x4); 1 x PCIe

2.0 x16 (x4 mode) *; 3rd/2nd/1st Gen AMD Ryzen™

Processors; 1 x PCIe 3.0 x16 (x4 mode); AMD B450 chipset;

3 x PCIe 2.0 x1; 1 x PCIe 3.0 x16 (x8 mode); AMD

Athlon™ with Radeon™ Vega Graphics

Processors

Storage: 3rd/2nd/1st Gen AMD Ryzen™ Processors : 1

x M.2_1 socket 3, with M key, type 2242/2260/2280 storage

devices support (SATA & PCIE 3.0 x 4 mode)*; 1 x

M.2_2 socket 3, with M key, type 2242/2260/2280/22110

storage devices support (PCIE 3.0 x 4 mode)*; 2nd and 1st

Gen AMD Ryzen™ with Radeon™ Vega Graphics

Processors : 1 x M.2_2 socket 3, with M Key, type

2242/2260/2280 storage devices support (SATA & PCIE

3.0 X2 mode); Total supports 2 x M.2 slot(s) and 6 x SATA

6Gb/s ports; 2 x SATA 3Gb/s port(s); 2 x SATA 6Gb/s port(s);

2 x SATA 6Gb/s port(s); AMD B450 chipset : 1 x M.2_1

socket 3, with M key, type 2242/2260/2280 storage devices

support (SATA & PCIE 3.0 x 4 mode); AMD

Athlon™ with Radeon™ Vega Graphics

Processors : 4 x SATA 6Gb/s port(s); Support Raid 0, 1, 10

Memory type: 4 x DIMM, Max. 128GB, DDR4

4400(O.C.)/4000(O.C.)/3866(O.C.)/3600(O.C.)/3466(O.C.)/3200

0/3000/2800/2666/2400/2133 MHz Un-buffered Memory

3rd/2nd/1st Gen AMD Ryzen™/ 2nd and 1st Gen AMD

Ryzen™ with Radeon™ Vega Graphics/

Athlon™ with Radeon™ Vega Graphics

Processors; Dual Channel Memory Architecture

I/O: 1 x Intel® I211-AT 1Gb Ethernet; 2 x USB 3.2 Gen 2;

3 x USB 3.2 Gen 1 Type-A; 1 x USB 3.2 Gen 1 USB

Type-C®; 1 x BIOS FlashBack™ Button(s); 1 x PS/2

keyboard/mouse combo port(s); 1 x DisplayPort; 1 x HDMI; 2

x USB 2.0; 1 x Optical S/PDIF out; 5 x Audio jack(s)

Connectors: 1 x M.2 Socket 2 with M key, type

2242/2260/2280/22110 storage devices support (PCIe 3.0 x 4 mode); 1 x USB 3.2 Gen 1 (up to 5Gbps) connector(s) support(s) additional 2 USB 3.2 Gen 1 port(s); 1 x M.2 Socket 1 with M key, type 2242/2260/2280 storage devices support (SATA & PCIe 3.0 x 4 mode); 1 x CPU Fan connector(s); 1 x CPU OPT Fan connector(s); 3 x Chassis Fan connector(s); 1 x AIO_PUMP connector; 1 x Addressable RGB header; 1 x AAFP connector; 2 x Aura RGB Strip Header(s); 1 x USB 2.0 connector(s) support(s) additional 2 USB 2.0 port(s); 1 x TPM header; 1 x COM port(s) connector(s); 6 x SATA 6Gb/s connector(s); 1 x 24-pin EATX Power connector(s); 1 x 8-pin ATX 12V Power connector(s); 1 x System panel(s); 1 x Thermal sensor connector(s); 1 x Clear CMOS jumper(s)

Audio: - Audio Shielding; ROG SupremeFX 7.1-Channel High Definition Audio CODEC S1220A; - Premium Japanese audio capacitors; - Audio Cover; - Optical S/PDIF out header(s) at mid-board; - Dual OP Amplifiers; - Impedance sense for front and rear headphone outputs; - Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking; - High quality 120dB SNR stereo playback output and 113dB SNR recording input; - Supports up to 32-Bit/192kHz playback *; Audio Feature : - SupremeFX Shielding & Trade Technology LAN: Intel® i211-AT 1Gb Ethernet; ASUS LANGuard BIOS: 256 Mb Flash ROM, UEFI AMI BIOS Form Factor: ATX Form Factor; 12 inch x 9.6 inch (30.5 cm x 24.4 cm) OS: Windows® 10 64-bit Warranty: 36 Months

Цена : 340.37 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пн 20 май, 2024