

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

## Dell EMC PowerSwitch N3248P-ON, 48x1G, 4x10G SFP+, 2x100G QSFP28, PoE 30W, 1xAC PSU, IO/PS, OS6, Lifetime Limited Hardware Warranty



Модел : DNN3248P

Dell EMC PowerSwitch N3248P-ON, 48x1G, 4x10G SFP+, 2x100G QSFP28, PoE 30W, 1xAC PSU, IO/PS, OS6, Lifetime Limited Hardware Warranty

Суич, тип: Fixed Port

Общ брой портове: 54

Основни портове, тип: 48x RJ45 10/100/1000Mb 802.3at

(up to 30W) PoE auto- sensing ports

Power Over Ethernet (PoE): 802.3at (30W) PoE

Uplink портове: 4x 10G SFP+

Свободни (10GB) слотове: -

Управление: CLI, Web, SNMP; 1x 10/100/1000BaseT

Ethernet management port

Stackable: 2x 100G QSFP28

Fans: 3 pluggable fan modules; Normal airflow only

Захранване: 1x 1050W AC PSU included; 2 pluggable AC

PSUs &mdash; 1 default and 1 optional or 2 optional DC

PSUs; 1 EPS (optional and connected from MPS-1S or MPS-3S power shelf)

Routing: Line-rate Layer 3 routing (Static routes: 1024

(IPv4)/1024 (IPv6); Dynamic routes: 8158 (IPv4)/4096 (IPv6);

RIP routing interfaces: 512, VLAN routing interfaces: 128)

Памет (Flash, RAM): 4 GB DDR4 SO-DIMM, 8 GB mSATA

2.0/M.2 SSD

Капацитет за маршрутизиране/превключване, Gbps: 576 Gbps

Пропускателна способност, Mpps: 800 Mpps

MAC адреси: 32K

VLAN (брой, стандарти): Private VLAN extensions and

Private VLAN Edge support; VLAN routing interfaces: 128;

VLANs supported: 4094; Protocol-based VLANs: Supported;

Max VLAN interfaces with ACLs applied: 24

QoS: DiffServ Field, DiffServ Architecture, Assured Fwd PHB,

Port Based QoS Services (TCP/UDP) Mode, Red/WRED, Flow

Based QoS Services, Audio Video Bridging Mode (IPv4/IPv6),

UDLD, srTCM, trTCM

L2 мрежови стандарти: 802.3ab 802.1ax (Layer 2) 802.1d,

802.1w, 802.1s, 802.1x (Mgmt/Security), 802.3x (Layer 2)

802.3 802.3ba (40 GbE and 100 GbE) 802.3bt 802.3at

802.3az 802.1v 1613 802.1p, 1q 802.1s 802.3u, 802.3bz,

802.3at

L3 мрежови стандарти: RIP, OSPF, VRRP, MIB  
IPv6 functionality: Layer 3 Advanced IPv4 and IPv6  
functionality including BGP, VRF, BFD, PIM-SM/DM/SSM,  
IGMP/MLD, RIPv1/v2, OSPFv2/v3  
Сигурност: RADIUS, TACACS+, 802.1x  
Размери (Ш, Д, В), mm: 434 x 400 x 43.5 mm  
Опция за монтаж: Rackmount, 1U  
Други: 1x Micro USB Type-B console port, 1x USB Type-A  
port, 1x RJ45 serial console port; Two-core Denveron-NS  
CPU

Цена : 14762.14 лв. с ДДС

*Наличност: Този продукт е бил добавен в нашия каталог на Пт 31 май, 2024*