

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

## Dell EMC N3208PX-ON, 4x1G RJ-45, 4x1/2.5/5G RJ-45, 2x10G SFP+, PoE 90W, 1xAC PSU, IO/PS, OS6, Lifetime Limited Hardware Warranty



Модел : DNN3208PX

Dell EMC N3208PX-ON, 4x1G RJ-45, 4x1/2.5/5G RJ-45, 2x10G SFP+, PoE 90W, 1xAC PSU, IO/PS, OS6, Lifetime Limited Hardware Warranty

Суич, тип: Fixed Port

Общ брой портове: 8

Основни портове, тип: 4x RJ45 10M/100M/1G/2.5G/5G

802.3bt (up to 90W) PoE autosensing ports + 4x 10M/100M/1000Mb 802.3bt (up to 90W) PoE autosensing ports

Power Over Ethernet (PoE): PoE

Uplink портове: 2x 10G SFP+ ports

Свободни (10GB) слотове: -

Управление: Management via an intuitive and familiar CLI, embedded web server (GUI), SNMP-based management console application (including Dell EMC OpenManage Network Manager), Telnet or serial connection.

Stackable: No

Fans: Redundant variable speed fans; Air flow: I/O to power supply

Захранване: 1x 320W AC PSU included

Routing: Line-rate Layer 3 routing; Static routes: 1024 (IPv4)/1024 (IPv6), Dynamic routes: 8158 (IPv4)/4096 (IPv6), OSPF routing interfaces: 8158, RIP routing interfaces: 512, ECMP next hops per route: 16, ECMP groups: 1024

Памет (Flash, RAM): 4 MB Buffer memory

Капацитет за маршрутизиране/превключване, Gbps: 88 Gbps

Пропускателна способност, Mpps: 122 Mpps

MAC адреси: 32K

VLAN (брой, стандарти): VLAN routing interfaces: 128;

VLANs supported: 4094; Protocol-based VLANs: Supported;

Max VLAN interfaces with ACLs applied: 24; IEEE compliance: Voice VLAN, 802.1Q, 802.1v, 802.1X

QoS: DiffServ Field, DiffServ Architecture, Assured Fwd PHB, Port Based QoS Services (TCP/UDP) Mode, Red/WRED, Flow Based QoS Services, Audio Video Bridging Mode (IPv4/IPv6), UDLD, srTCM, trTCM

L2 мрежови стандарти: IEEE 802.3bt

L3 мрежови стандарти: RIPv1, RIPv2 MIB Extension, OSPF DB overflow, OSPF MIB, RIP-2 MD5 Auth, OSPFv2, VRRP,



Opaque, Policy Based Routing, RIPv2, OSPFv3, VRRP MIB, NSSA, OSPF Stub Router Advert, Graceful Restart, VRRP, BGP, OSPFv3

IPv6 functionality: BGP, VRF, BFD, PIM-SM/DM/SSM, IGMP/MLD, RIPv1/v2, OSPFv2/v3

Сигурност: AAA authorization, TACACS+ accounting and RADIUS

Размери (Ш, Д, В), mm: 279.4 x 312 x 43.5 mm

Опция за монтаж: Rackmount (1U)

Цена : 7510.15 лв. с ДДС

*Наличност: Този продукт е бил добавен в нашия каталог на Пн 24 юни, 2024*