

КОМПЮТРИ И СЪРВЪРИ > Сервъри

Dell PowerEdge T350, Chassis 8 x 3.5 HotPlug, Xeon E-2314 (2.8GHz, 8MB, 4C/4T), 16GB UDIMM 3200MT/s ECC, 1x2TB SATA 7.2K, Bezel, Broadcom 5720 Dual, PERC H355 Adapter FH, iDRAC9 Basic 15G, Single Hot Plug PSU 600W, TPM 2.0 V3, 3Y Basic Next Business Day



Модел : PET350CM1

Dell PowerEdge T350, Chassis 8 x 3.5 HotPlug, Xeon E-2314 (2.8GHz, 8MB, 4C/4T), 16GB UDIMM 3200MT/s ECC, 1x2TB SATA 7.2K, Bezel, Broadcom 5720 Dual, PERC H355 Adapter FH, iDRAC9 Basic 15G, Single Hot Plug PSU 600W, TPM 2.0 V3, 3Y Basic Next Business Day

Серия: PowerEdge T350

Процесор: Intel Xeon E-2314 2.8GHz, 8M Cache, 4C/4T, Turbo (65W), 3200 MT/s

Памет, GB: 16GB UDIMM, 3200MT/s, ECC

Памет, слотове: 4 DDR4 DIMM slots, supports UDIMM 128 GB max, speeds up to 3200 MT/s

Твърд диск, GB: 1x2TB

Дисков контролер: PERC H355 Adapter

Брой поддържани дискове: Up to 8 x 3.5" SAS/SATA (HDD/SSD) max 128 TB (Also supports 2.5-inch drive in 3.5-inch hybrid drive carrier)

Оптично устройство: -

Мрежа: Broadcom 5720 Dual Port

Разширителен слот: 2 x Gen 4 PCIe slots, 2 x Gen3 PCIe slots

Интерфейс: Network Options: 2 x 1 GbE LOM, Front: 1x iDRAC Direct (Micro-AB USB) port, 1x USB 3.0, 2x USB 2.0; Rear: 1x USB 2.0, 1x USB 3.0, 1x Serial, 1x iDRAC, 1x VGA; Internal: 1 x USB 3.0 (optional); 1x VGA

Порт за отдалечено управление: yes

Захранване: 450 W Bronze (cabled) AC/100 - 240 V

Съвместими операционни системи: Canonical Ubuntu Server LTS, Citrix Hypervisor, Microsoft Windows Server with Hyper-V, Red Hat Enterprise Linux, SUSE Linux Enterprise Server

Софтуер за управление: iDRAC9 Basic 15G

Форм-фактор: 4.5U Tower

Тип на шасито: Hot-Plug

Други: One fan, Bezel

Цена : 4412.21 лв. с ДДС



Наличност: Този продукт е бил добавен в нашия каталог на Чт 16 май, 2024

November 24, 2024, 4:28