

КОМПЮТРИ И СЪРВЪРИ > Сървъри

Dell PowerEdge T350, Intel Xeon E-2378 2.6GHz, 16MB, 8C/16T, 16GB UDIMM, 3200MT/s, ECC, 3.5" Chassis up to 8 Hot Plug HDD and AIC PERC, HBA355i, 2x 2TB 7.2K RPM NLSAS ISE 3.5in HDD, Dual Redundant PSU (1+1) 600W, BOSS Blank, iDRAC9 Basic 15G, 36M



Модел : 210-BBSR

Dell PowerEdge T350, Intel Xeon E-2378 2.6GHz, 16MB, 8C/16T, 16GB UDIMM, 3200MT/s, ECC, 3.5" Chassis up to 8 Hot Plug HDD and AIC PERC, HBA355i, 2x 2TB 7.2K RPM NLSAS ISE 3.5in HDD, Dual Redundant PSU (1+1) 600W, BOSS Blank, iDRAC9 Basic 15G, 36M

Серия: PowerEdge T350

Процесор: Intel Xeon E-2378 2.6GHz, 16M Cache, 8C/16T, Turbo (65W), 3200 MT/s

Памет, GB: 16GB UDIMM, 3200MT/s, ECC

Памет, слотове: 4 DDR4 DIMM slots, supports UDIMM 128 GB max, speeds up to 3200 MT/s

Твърд диск, GB: 2x 2TB 7.2K RPM NLSAS ISE 12Gbps 512n 3.5in Hard Drive

Дисков контролер: HBA355i Adapter, Full Height

Брой поддържани дискове: 3.5" Chassis with up to 8 Hot Plug Hard Drives and AIC PERC, hot-plug PSU

Оптично устройство: -

Мрежа: Broadcom 5720 Dual Port

Разширителен слот: 2 x Gen 4 PCIe slots, 2 x Gen3 PCIe slots

Интерфейс: Network Options: 2 x 1 GbE LOM, Front: 1x iDRAC Direct (Micro-AB USB) port, 1x USB 3.0, 2x USB 2.0; Rear: 1x USB 2.0, 1x USB 3.0, 1x Serial, 1x iDRAC, 1x VGA; Internal: 1 x USB 3.0 (optional); 1x VGA

Порт за отдалечено управление: yes

Захранване: Dual, Hot-Plug, Redundant Power Supply (1+1), 600W

Съвместими операционни системи: Canonical Ubuntu Server LTS, Citrix Hypervisor, Microsoft Windows Server with Hyper-V, Red Hat Enterprise Linux, SUSE Linux Enterprise Server

Софтуер за управление: iDRAC9 Basic 15G

Форм-фактор: 4.5U Tower

Тип на шасито: Hot-Plug

Други: One fan, Bezel

Цена : 5887.44 лв. с ДДС



Наличност: Този продукт е бил добавен в нашия каталог на Чт 16 май, 2024

November 24, 2024, 7:57 AM