

КОМПЮТРИ И СЪРВЪРИ > Сървъри

Dell PowerEdge R7515 Server, AMD EPYC 7402P 2.8GHz, 24C/48T, 128MB L3 Cache, 180W, 2x 32GB RDIMM 3200MT/s, Dual Rank 16Gb x8, iDRAC9 Express 15G, 3.5" Chassis with up to 8 Drives, 2x 960GB SSD S3 Read Intensive, PERC H730P, Dual PSU 750W Titanium, 36M NB



Модел : 210-ASVQ

Dell PowerEdge R7515 Server, AMD EPYC 7402P 2.8GHz, 24C/48T, 128MB L3 Cache, 180W, 2x 32GB RDIMM 3200MT/s, Dual Rank 16Gb x8, iDRAC9 Express 15G, 3.5" Chassis with up to 8 Drives, 2x 960GB SSD S3 Read Intensive, PERC H730P, Dual PSU 750W Titanium, 36M NB

Серия: PowerEdge R7515

Процесор: AMD EPYC 7402P 2.8GHz, 24C/48T, 128MB L3 Cache, 180W

Памет, GB: 2x 32GB RDIMM 3200MT/s, Dual Rank 16Gb x8

Памет, слотове: 16 DDR4 RDIMM/LRDIMM slots, Type: RDIMM/LDIMM, Up to 3200MT/s, Max. RAM: RDIMM - 1TB, LRDIMM - 2TB

Твърд диск, GB: 2x 960GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 3.5in HYB CARR, 1 DWPD

Дисков контролер: PERC H730P RAID Controller, 2GB NV Cache, Mini card

Брой поддържани дискове: 8xLFF (3.5" Chassis with up to 8 Drives)

Оптично устройство: -

Мрежа: 2x 1GbE, 2x 10GbE BT, 2x 10GbE SFP+, 2x 25GbE SFP28

Разширителен слот: No PCIe Riser; Up to 4: 2x Gen3 slots (1 x8; 1 x16), 2x Gen4 slots (2 x16)

Интерфейс: Front: 1x Dedicated iDRAC direct micro-USB, 2x USB 2.0, 1x Video; Rear: 2x 1GbE, 1x Dedicated iDRAC network port, 1x Serial, 2x USB 3.0, 1x Video

Порт за отдалечено управление: yes

Захранване: Dual, Hot-plug, Redundant Power Supply (1+1), 750W, Titanium, 200-240VAC

Съвместими операционни системи: Canonical Ubuntu Server LTS, Citrix Hypervisor™, Microsoft Windows Server with Hyper-V, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi

Софтуер за управление: iDRAC9 Express 15G

Форм-фактор: 2U Rack

Тип на шасито: Hot-Plug

Други: 6 Fans



Цена : 12886.79 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 22 май, 2024