

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Cisco Catalyst 9300 24-port 1G copper, with fixed 4x1G SFP uplinks, PoE+ Network Essentials



Модел : C9300L-24P-4G-E

Cisco Catalyst 9300 24-port 1G copper, with fixed 4x1G SFP uplinks, PoE+ Network Essentials

Суич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 24x10/100/1000Base-T

Power Over Ethernet (PoE): 24 PoE+; Available PoE power: 505W

Uplink портове: 4x10/100/1000Base-T

Свободни (10GB) слотове: No

Управление: SNMPv1, SNMPv2c, and SNMPv3; RMON I and II standards; Internet Group Management Protocol (IGMP); CLI; TCP; UDP

Stackable: Stacking support: StackWise-320; 320 Gbps;

Optional Stacking hardware: C9300L-STACK-KIT; Number of members: 8; Supported stack members: Other C9300L SKUs with same license level

Fans: three field-replaceable fans and support (N+1) redundancy

Захранване: Dual redundant power supplies, Default primary AC power supply: PWR-C1-715WAC-P

Routing: Layer 3 Advanced

Памет (Flash, RAM): Flash memory: 16 GB; 8 GB DRAM

Капацитет за маршрутизиране/превключване, Gbps: 56 Gbps; Switching capacity with stacking: 376 Gbps

Пропускателна способност, Mpps: 41.66 Mpps; Forwarding rate with stacking: 279.76 Mpps

MAC адреси: 32000 MAC address

VLAN (брой, стандарти): VLAN IDs: 4094; IEEE 802.1Q VLAN

QoS: Granular wireless bandwidth management and fair sharing, 802.1p Class of Service (CoS) and Differentiated Services Code Point (DSCP) field classification, Shaped Round Robin (SRR) scheduling, Committed Information Rate (CIR), and eight egress queues per port

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3bz, IEEE 802.3ad, IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.1x-Rev, IEEE 802.3x

L3 мрежови стандарти: IP unicast routing protocols: Static, Routing Information Protocol Version 1 [RIPv1], and RIPv2, RIPvng, Open Shortest Path First [OSPF]



IPv6 functionality: IPv6 routing (using OSPFv3 and EIGRPv6) is supported in hardware for maximum performance; IPv6 addressing is supported on interfaces with appropriate show commands for monitoring and troubleshooting

Сигурност: Enhanced security with AES-128 MACsec encryption, policy-based segmentation, and trustworthy systems

Размери (Ш, Д, В), mm: 44.5 x 44.9 x 4.4

Опция за монтаж: Rackmount

Други: Задължителен е минимум 3-годишен лиценз DNA Essentials.

Цена : 5303.99 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 17 юли, 2024