

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 24 ports GE + 2 10GE ports + 2 SFP+ Smart Managed Switch



Модел : DGS-1520-28

D-Link 24 ports GE + 2 10GE ports + 2 SFP+ Smart Managed Switch

Суич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 24x10/100/1000Base-T

Power Over Ethernet (PoE): -

Uplink портове: 2x10GBase-T, 2x10G SFP+

Свободни (10GB) слотове: No

Управление: Web-based GUI, CLI, SNMP; DHCP, DDP, SMTP;

Telnet Server/Client for IPv4/IPv6 TFTP Client; TFTP/DNS

Client for IPv4/IPv6; Secure FTP Server/Client for IPv4/IPv6

SNMP; RMON; BootP/DHCP Client; ZTP etc.

Stackable: Physical stacking: 10GBase-T and SFP+, Up to 8

units per stack, Up to 80 Gbps stacking bandwidth,

Ring/chain topology support; Virtual stacking: D-Link Single

IP Management (SIM), Up to 32 units per virtual stack

Fans: -

Захранване: 100 - 240 VAC; Max. Power Consumption: 30.4

W

Routing: Dynamic Layer 3 routing

Капацитет за маршрутизиране/превключване, Gbps: 128

Gbps

Пропускателна способност, Mpps: 95.24 Mbps

MAC адреси: Up to 16,384 entries per device; Up to 512

static MAC entries

VLAN (брой, стандарти): VLAN Group (Max. 4K VLAN

groups, Max. 1~4094 VIDs); GVRP - Max. 4K dynamic VLAN

groups; Double VLAN (Q-in-Q); Selective Q-in-Q; 802.1Q;

Auto

Surveillance/Port-based/Voice/MAC-based/Multicast/Subnet-

based/Asymmetric/Private VLAN; 802.1v Protocol-based

VLAN

QoS: 802.1p; 8 queues per port; Queue Handling;

Congestion Control; Policy Map; CoS based on: Switch port,

Inner/Outer VID, Inner/Outer 802.1p Priority, MAC address,

Ether type, IP address etc, Bandwidth Control; Three Color

Marker

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE

802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3az, IEEE

802.3x, IEEE 802.3ae.

L3 мрежови стандарти: IGMP v1/v2/v3, IGMP Proxy, MLD

v1/v2, MLD proxy, DVMRP v3, PIM Sparse-Dense Mode

(PIM-SDM), PIM-SM/DM/SSM for IPv4/IPv6
IPv6 functionality: IPv4/IPv6 access; Telnet Server/Client,
TFTP/DNS Client, Secure FTP Server/Client; Ping/ Traceroute;
IPv6 Snooping; IPv6 Route Advertisement (RA) Guard; IPv6
ND Inspection; IPv6 Traffic Class; IPv6 Flow Label
Сигурност: Port Security (Supports up to 64 MAC addresses
per port), Broadcast/Multicast/Unicast Storm Control, D-Link
Safeguard Engine, DHCP Server Screening, IP Source Guard,
DHCP/IPv6 Snooping, DAI, ARP Spoofing Prevention, SSL,
SSH, BPDU Attack Protection etc.
Размери (Ш, Д, В), mm: 207.4 x 441 x 44 mm
Опция за монтаж: Rackmount
Други: Auto or configurable MDI/MDIX

Цена : 1456.28 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 17 юли, 2024