

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

ZyXEL XS3800-28, 28-port 10GbE L2+ Managed Switch Nebula Flex Pro (dual AC, 1 year NCC Pro pack license bundled)



Модел : XS3800-28-ZZ0101F

ZyXEL XS3800-28, 28-port 10GbE L2+ Managed Switch Nebula Flex Pro (dual AC, 1 year NCC Pro pack license bundled)

Суич, тип: Flexible Port

Общ брой портове: 28

Основни портове, тип: 4x 100M/1G/2.5G/5G/10G Ethernet (RJ-45)

Power Over Ethernet (PoE): -

Uplink портове: 8x Multi-Gigabit combo

(100M/1G/2.5G/5G/10G) RJ-45/SFP+

Свободни (10GB) слотове: 16x 10-Gigabit SFP+

Управление: Standalone management by Web interface, Cloud management by Nebula Control Center, iStacking, CLI, DHCP, Management through console, telnet, SNMP

Stackable: Physical stacking up to 4 units

Fans: -

Захранване: Internal (100 - 240 V AC, 50/60 Hz)

Routing: Static (Routing table: 1K), Basic Routing License

RIP v1/v2, Basic Routing License OSPFv2, Basic Routing License DVMRP

Памет (Flash, RAM): 64 MB/8 GB (Flash/RAM)

Капацитет за маршрутизиране/превключване, Gbps: 560 Gbps

Пропускателна способност, Mpps: 416 Mpps

MAC адреси: 32 K

VLAN (брой, стандарти): 802.1Q static VLANs/dynamic

VLANs: 4 K/4 K; Port-based/Vendor

ID-based/Protocol-based/IP subnet-based/Private VLAN;

VLAN trunking; VLAN translation; VLAN ingress filtering;

802.1ad VLAN stacking (Q-in-Q); LACP algorithm of source/destination IP; GVRP; L2P

QoS: 8 queues per Port, 802.1p queuing method:

SPQ/WRR/WFQ; Storm control: Broadcast, Multicast,

Unknown Unicast (DLF); Port-based rate limiting; Rate

limiting, per IP/TCP/UDP per port, Policy-based rate limiting,

802.3x flow control; 802.1p CoS; DSCP

L2 мрежови стандарти: IEEE 802.3z, IEEE 802.3ab, IEEE

802.3ap, IEEE 802.3ae, IEEE 802.3bz, IEEE 802.3az, IEEE

802.3x, IEEE 802.1p, IEEE 802.1ab, IEEE 802.3ah

L3 мрежови стандарти: IEEE 802.1d, IEEE 802.1w, IEEE

802.1s, IEEE 802.3ad, ECMP, VRRP

IPv6 functionality: IPv6 over Ethernet, IPv6 addressing

architecture; Dual stack; ICMPv6; Path MTU; Minimum path MTU size of 1280; Encapsulation for minimum MTU of 1500; Neighbor discovery; DHCPv6 Relay

Сигурност: 802.1x; Port security; MAC authentication; Layer 2 MAC filtering; Layer 3 IP filtering; Layer 4 TCP/UDP socket filtering; BPDU transparency; Static MAC forwarding; RADIUS; TACACS+; SSH v2; SSL; DHCP; ARP; Policy-based security filtering

Размери (Ш, Д, В), mm: 441 x 360 x 44 mm

Опция за монтаж: Rackmount

Цена : 8745.67 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 08 август, 2024