

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Aruba 6000 48G CL4 4SFP Swch



Модел : R8N85A

Aruba 6000 48G CL4 4SFP Swch

Суич, тип: Fixed Port

Общ брой портове: 52

Основни портове, тип: 48x 10/100/1000BASE-T Ports

Power Over Ethernet (PoE): 370W Class 4 PoE/PoE+ (IEEE 802.3af, 802.3at)

Uplink портове: 4x 1G/10G SFP ports

Свободни (10GB) слотове: -

Управление: Management flexibility with support for Aruba Central, easy-to-use Web GUI, CLI, and Aruba NetEdit

Stackable: -

Fans: Fixed fans

Захранване: Fixed power supply (100-127 VAC / 200-240 VAC, 4.9 A / 2.4 A); Power Consumption (230 VAC): Idle: 30.6W Max Power (w/o PoE): 45W Max Power (w/ PoE): 480W

Routing: Static (Layer 3): Static IP routing provides manually configured routes, Dual stack static IPv4 and IPv6 routing provides simple manually configured IPv4 and IPv6 routing, Dual IP stack maintains separate stacks for IPv4 and IPv6

Памет (Flash, RAM): 4 GB DDR3, 16 GB eMMC; Packet Buffer: 12.38MB (4.5MB Ingress/7.875MB Egress)

Капацитет за маршрутизиране/превключване, Gbps: 104 Gbps

Пропускателна способност, Mpps: 77.3 Mpps

MAC адреси: 8 192

VLAN (брой, стандарти): VLAN support and tagging support for IEEE 802.1Q (4094 VLAN IDs) and 512 VLANs simultaneously

QoS: Strict priority (SP) queuing, Traffic prioritization (IEEE 802.1p) for real-time classification, CoS sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), Layer 3 protocol, TCP/UDP port number, source port, and DiffServ

L2 мрежови стандарти: RFC 1591 DNS (client), SSHv1/SSHv2 Secure Shell, IEEE 802.1D MAC Bridges, IEEE 802.1p Priority, IEEE 802.1Q VLANs, IEEE 802.1s Multiple Spanning Trees, IEEE 802.1w Rapid Reconfiguration of Spanning Tree, IEEE 802.3 Type 10BASE-T, IEEE 802.3ab IPv6 functionality: IPv6 host enables switches to be managed in an IPv6 network; Dual stack (IPv4 and IPv6) transitions from IPv4 to IPv6; MLD snooping forwards IPv6

multicast traffic to the appropriate interface; IPV6 static routing and etc.

Сигурност: ACL, RADIUS, TACACS+, 802.1X, Web, and MAC authentications, CLI, GUI, or MIB through SSHv2, SSL, and/or SNMPv3, STP BPDU port protection, SSL and etc.

Размери (Ш, Д, В), mm: 442 x 304.8 x 43.9 mm

Опция за монтаж: Rackmount (1U)

Други: Includes Mounting Brackets; 1x USB-C Console Port, 1x USB Type-A Host port

Цена : 2918.03 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пт 17 октомври, 2025