

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

ZyXEL XGS2220-54FP, L3 Access Switch, 960W PoE, 40xPoE+/10xPoE++, 48x1G RJ45 2x10mG RJ45, 4x10G SFP+ Uplink, incl. 1 yr NebulaFlex Pro



Модел : XGS2220-54FP-EU0101F

ZyXEL XGS2220-54FP, L3 Access Switch, 960W PoE, 40xPoE+/10xPoE++, 48x1G RJ45 2x10mG RJ45, 4x10G SFP+ Uplink, incl. 1 yr NebulaFlex Pro
Суич, тип: Fixed Port, Layer 3 Access

Общ брой портове: 54

Основни портове, тип: 48x 10/100/1000Base-T

Power Over Ethernet (PoE): 50 PoE ports: 40x Gigabit RJ-45 PoE+ ports + 8x Gigabit RJ-45 PoE++ (60 W) ports + 2x 10G Multi-Gigabit (1G/2.5G/5G/10G) RJ-45 PoE++ (60 W) ports;
PoE power budget: 960 W

Uplink портове: 4x 1G SFP/10G SFP+ slots + 2x10G Multi-Gigabit (1G/2.5G/5G/10G) RJ-45 ports

Свободни (10GB) слотове: -

Управление: Standalone management by Web interface;

Cloud management by Nebula Control Center; Management through Console, Telnet, SNMP; Multilevel CLI; DHCP

Stackable: Physical stacking (In the future firmware release)

Fans: 1 x smart fan

Захранване: 100 - 240 V AC, 50/60 Hz; Max. power consumption: 1161.6W

Routing: Static; Static route: 64

Памет (Flash, RAM): 64 MB/1 GB (Flash/RAM)

Капацитет за маршрутизиране/превключване, Gbps: 261 Gbps

Пропускателна способност, Mpps: 161 Mpps

MAC адреси: 32 K

VLAN (брой, стандарти): 802.1Q static VLANs/dynamic

VLANs: 4 K/4 K; VLAN isolation; Port-based/Vendor ID based/Protocol-based/IP

subnet-based/MAC-based/Private/Voice VLAN; Independent VLAN Learning (IVL); VLAN Translation/trunking/mapping; QinQ; GVRP; L2PT

QoS: No. of hardware queues per port

(Standalone/stacking): 8*/6; Storm control and event log;

Port-based rate limiting; Rate limiting per IP/TCP/UDP per

port; Policy-based rate limiting; 802.3x flow control; 802.1p

Class of Service; DSCP

L2 мрежови стандарти: IEEE 802.3z, IEEE 802.3ab, IEEE 802.3an, IEEE 802.3ae, IEEE 802.1X

L3 мрежови стандарти: IEEE 802.1D Spanning Tree

Protocol (STP); IEEE 802.1w Rapid Spanning Tree Protocol (RSTP); IEEE 802.1s Multiple Spanning Tree Protocol (MSTP); IEEE 802.3ad LACP

IPv6 functionality: Max. 1 K IPv4 entries; Max. 512 IPv6 entries; IP source guard (IPv4*/IPv6); ACL packet filtering (IPv4/IPv6); Syslog (IPv4/IPv6); IPv6 over Ethernet (RFC 2464); IPv6 addressing architecture (RFC 4291); IPv6 binding- static/dynamic

Сигурност: Port security; Layer 2 MAC filtering; Layer 3 IP filtering; Layer 4 TCP/UDP socket filtering; Static MAC forwarding; RADIUS; TACACS+; SSH v2; SSL; DHCP;

Размери (Ш, Д, В), mm: 441 x 330 x 44 mm

Опция за монтаж: Rackmount

Други: Rack mounting kit included; incl. 1 yr NebulaFlex Pro

Цена : 3762.34 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пт 03 януари, 2025