

КОМПЮТРИ И СЪРВЪРИ > Сервъри

Dell PowerEdge R7515, Chassis 8 x 3.5" Hot Plug, AMD EPYC 7232P 3.10GHz (8C/16T, 32M), 16GB 3200MT/s RDIMM Dual Rank, 480GB SATA SSD, Rails w/o arm, Bezel, No Riser, PERC H740P mini, iDRAC9 Enterprise 15G, Dual 1100W PSU, 3Y Basic Onsite



Модел : PER751501B

Dell PowerEdge R7515, Chassis 8 x 3.5" Hot Plug, AMD EPYC 7232P 3.10GHz (8C/16T, 32M), 16GB 3200MT/s RDIMM Dual Rank, 480GB SATA SSD, Rails w/o arm, Bezel, No Riser, PERC H740P mini, iDRAC9 Enterprise 15G, Dual 1100W PSU, 3Y Basic Onsite

Серия: PowerEdge R7515

Процесор: AMD EPYC 7232P (3.10GHz, 8C/16T, 32MB Cache, 120W)

Памет, GB: 16GB 3200MT/s RDIMM Dual Rank

Памет, слотове: 16 DDR4 RDIMM/LRDIMM slots, Type: RDIMM/LDIMM, Up to 3200MT/s, Max. RAM: RDIMM - 1TB, LRDIMM - 2TB

Твърд диск, GB: 480GB SSD SATA Read Intensive 6Gbps 512 2.5in Hot-plug AG Drive, 3.5in HYB CARR, 1 DWPD

Дисков контролер: PERC H740P RAID Controller, 8GB NV Cache, Mini card

Брой поддържани дискове: Chassis 8 x 3.5" Hot Plug

Оптично устройство: -

Мрежа: 2 x 1Gb Onboard LOM (BCM5720) MLK; Trusted Platform Module 2.0 V3

Разширителен слот: No PCIe Riser; Up to 4: 2x Gen3 slots (1 x8; 1 x16), 2x Gen4 slots (2 x16)

Интерфейс: Front: 1x Dedicated iDRAC direct micro-USB, 2x USB 2.0, 1x Video; Rear: 2x 1GbE, 1x Dedicated iDRAC network port, 1x Serial, 2x USB 3.0, 1x Video

Порт за отдалечено управление: yes

Захранване: Dual, Hot-plug, Redundant Power Supply (1+1), 1100W

Съвместими операционни системи: Canonical Ubuntu Server LTS, Citrix Hypervisor™, Microsoft Windows Server with Hyper-V, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi

Софтуер за управление: iDRAC9 Enterprise 15G

Форм-фактор: 2U Rack

Тип на шасито: Hot-Plug

Други: Rails w/o arm, Bezel



Цена : 6454.03 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пн 12 февруари, 2024