

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Cisco CBS350 Managed 12-port 10GE, 2x10G SFP+ Shared



Модел : CBS350-12XT-EU

Cisco CBS350 Managed 12-port 10GE, 2x10G SFP+ Shared

Суич, тип: Fixed Port, Managed

Общ брой портове: 12

Основни портове, тип: 10x10GBase-T

Power Over Ethernet (PoE): -

Uplink портове: 2x10 Gigabit SFP+ (combo with 2 x 10G copper ports)

Свободни (10GB) слотове: -

Управление: 1x GE OOB management; Web user interface; Cisco Business Dashboard; CLI; SNMP

Stackable: Up to 4 units in a stack. Up to 192 ports managed as a single system with hardware failover

Fans: 2

Захранване: Internal (100-240V, 50-60 Hz)

Routing: Layer 3 RIP

Памет (Flash, RAM): Flash: 256 MB; CPU memory: 512 MB,

Packet buffer: 3 MB

Капацитет за маршрутизиране/превключване, Gbps: 240 Gbps

Пропускателна способност, Mpps: 178.56 Mpps

MAC адреси: 16K

VLAN (брой, стандарти): Support for up to 4094 VLANs simultaneously; Port-based and 802.1Q tag-based VLANs;

MAC/protocol-based VLAN; IP subnet-based/Management

VLAN; Private VLAN; PVE; Guest/unauthenticated VLAN;

Dynamic VLAN assignment via RADIUS server;

Voice/Multicast TV VLAN

QoS: Priority levels: 8 hardware queues; Scheduling: Strict

priority and Weighted Round-Robin (WRR); Class of service:

Port based; 802.1p VLAN priority-based; IPv4/v6 IP

precedence/Type of Service (ToS)/DSCP-based; DiffServ;

ACLs, trusted QoS

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE

802.3ab, IEEE 802.3ad, IEEE 802.3z, IEEE 802.3x Flow

Control, IEEE 802.3 ad LACP, IEEE 802.1D (STP), IEEE

802.1Q/p VLAN, IEEE 802.1w RSTP, IEEE 802.1s Multiple STP,

IEEE 802.1X, IEEE 802.3af, IEEE 802.3at, RFC

L3 мрежови стандарти: Support for Routing Information

Protocol version 2 for dynamic routing

IPv6 functionality: IPv6 host mode; IPv6 over Ethernet; Dual

IPv6/IPv4 stack; IPv6 neighbor and router discovery (ND);

IPv6 stateless address autoconfiguration; MTU discovery;

DAD; ICMP v6; DHCPv6 stateful client; ISATAP
Сигурност: SSH v1/v2; SSL; IEEE 802.1X; Web-based authentication; IP Source Guard; Dynamic ARP Inspection (DAI); IP/MAC/Port Binding (IPMB); Secure Core Technology (SCT); Secure Sensitive Data (SSD); Port security; RADIUS/TACACS+; RADIUS accounting; Storm control
Размери (Ш, Д, В), mm: 440 x 203 x 44 mm
Опция за монтаж: Rackmount
Други: Cisco standard RJ45 console port; USB Type-A slot on the front panel of the switch for easy file and image management

Цена : 3172.76 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пн 04 март, 2024