

ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

HikVision IP Dome Camera 6 MP, 2.8 mm, IR up to 30m, H.265+, IP67, built-in microphone, 12Vdc/PoE 7.5W



Модел : DS-2CD2363G2-IU

HikVision IP Dome Camera 6 MP, 2.8 mm, IR up to 30m, H.265+, IP67, built-in microphone, 12Vdc/PoE 7.5W

Тип: IP

Сензор, тип: CMOS

Размер на оптичния сензор: 1/2.8" Progressive Scan CMOS

Резолюция, MP: 6 MP

Фокално разстояние: 2.8 mm, horizontal FOV 107°, vertical FOV 57°, diagonal FOV 128°

Минимална осветеност, lx: Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR

IR осветление: Up to 30 m

Максимална резолюция, pixels: 3200x1800

Формати на компресиране: Main stream:

H.265/H.264+/H.264/H.265+; Sub-stream:

H.265/H.264/MJPEG Third stream: H.265/H.264; Audio

Compression: -U:

G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/MP3/AAC-LC

Скорост на предаване на кадри: Main Stream: 50 Hz: 20 fps (3200 x 1800) 25 fps (2688 x 1520, 1920 x 1080, 1280 x 720); 60 Hz: 20 fps (3200 x 1800) 30 fps (2688 x 1520, 1920 x 1080, 1280 x 720)

Поддържани мрежови протоколи: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, WebSocket, WebSockets, SRTP, SFTP, RTCP

Мрежов интерфейс: 1 RJ45 10 M/100 M self-adaptive Ethernet port

Безжична мрежа: -

Power Over Ethernet (PoE): PoE: IEEE 802.3af, Class 3, max. 7.5 W

Входни/Изходни портове: -

Звук: Built-In Microphone

Захранване: 12 VDC \pm 25%, 0.5 A, max. 6 W, Ш5.5 mm coaxial power plug, reverse polarity protection

Слот за карти: Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB

Нощно виждане: IR cut filter

Външен монтаж: Aluminum alloy body

Влагозащита: IP67

Вандалоустойчивост: -
Работна температура: -30 °C to 60 °C
Диапазон на влажността при експлоатация: Humidity 95% or less (non-condensing)
Сигурност: Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-TLS, EAP-LEAP, EAP-MD5), watermark, IP address filter, basic and digest authentication for HTTP/HTTPS, WSSE and digest authentication for Open Network Video Interface
Размери (Ш, Д, В), mm: D127.3 mm x 95.9 mm
Допълнителни функции: Heartbeat, mirror, password reset via email, pixel counter, anti-banding; Motion detection (support alarm triggering by specified target types (human and vehicle)), video tampering alarm, exception; Line crossing detection, intrusion detection
Други: Upload to FTP/memory card/NAS, notify surveillance center, trigger recording, trigger capture, send email

Цена : 410.71 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пт 25 октомври, 2024