

МРЕЖОВА ТЕХНИКА > Други

Cisco Room Bar in First Light w/Navigator (Table Stand)



Модел : CS-BAR-T-K9

Cisco Room Bar in First Light w/Navigator (Table Stand)

Резолюция: Video output: Live video resolutions (encode and decode) up to 1920 x 1080 at 30 fps and 60 fps;

Content stream - Supports resolutions up to 3840 x 2160 at 15 fps

Размер на екрана, inch: -

Видео стандарти: H.263, H.264

Видео вход: 1x HDMI input supports formats up to maximum 3840 x 2160 at 30 fps, including 1920 x 1080 at 60 fps; 1x USB-C input supports formats up to maximum 3840 x 2160 at 30 fps, including 1920 x 1080 at 60 fps

Видео изход: 2x HDMI outputs supporting formats up to 3840 x 2160 at 60 fps

Аудио стандарти: G.711, G.722, G.722.1, G.729, AAC-LD, and Opus

Аудио вход: 1x HDMI, 1x analog microphone input, 1x DisplayPort/USB-C input, 1x USB-A input; Bluetooth - Not available on Non Radio Version

Аудио изход: 1x DisplayPort/USB-C output, 1x USB-A output; Bluetooth - Not available on Non Radio Version

Камера: 12MP camera, 30 frames per second, 1/2.3" CMOS, 5x digital zoom, f/2.5 aperture, 120° horizontal field of view, 95° vertical field of view, Auto framing (face detect), Speaker tracking, Auto brightness and white balance, Fixed focus

Протоколи: Content stream: Binary Floor Control Protocol (BFCP) Session Initiation Protocol (SIP) dual stream;

Protocols: H.323, SIP, Webex, WebRTC; IP network: Date and time support using Network Time Protocol (NTP), IPv4 DHCP, CDP

Мултисайт: 4-way embedded SIP/H.323 conferencing capability with MultiSite option; Features: Up to 15 Mbps total MultiSite bandwidth (6 Mbps in point-to-point calls), Adaptive SIP/H.323 MultiSite, Full individual audio and video transcoding, H.323/SIP/VoIP

Мрежови интерфейси: 1x Ethernet (RJ-45) 100/1000 Mbps for LAN (external network); 1x Ethernet (RJ-45) 100/1000 Mbps PoE port enabled for Cisco Room Navigator touch panel direct pairing; Wi-Fi 802.11a/b/g/n/ac 2.4 GHz/5 GHz, 2x2 Multiple-Input Multiple Output (MIMO)

Други интерфейси: Bluetooth and BT Low Energy; 1 USB 2.0 port type A (for USB microphone or other room

peripherals); 1 micro-USB port (service port); Factory reset pinhole; Ability to provide camera, microphone, and speakers over one USB-C cable to a connected computer

Консумация, W: 100 to 240 VAC, 50/60 Hz, 12V DC input; Average 20W, peak 86W; Must be used with power supply PSU-12VDC-86W

Размери (Ш, Д, В), cm: 53.4 x 6.4 x 8.2 cm

Цена : 5729.74 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 13 ноември, 2024