

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

GB B650 GAMING X / AM5



Модел : GB B650 GAMING X / AM5

GB B650 GAMING X / AM5

CPU's supported: AMD Socket AM5, support for: AMD Ryzen™; 7000 Series Processors

Memory type: Support for DDR5 8000(OC)/ 7800(OC)/ 7600(OC)/ 7200(OC)/ 7000(OC)/ 6800(OC)/ 6600(OC)/ 6400(OC)/ 6200(OC)/ 6000(OC)/ 5600(OC)/ 5200/ 4800 MT/s memory modules; 4 x DDR5 DIMM sockets supporting up to 192 GB (48 GB single DIMM capacity) of system memory; Dual channel memory architecture; Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules; Support for AMD EXPO™ (AMD EXPO™) and Extreme Memory Profile (XMP) memory modules

Chipset: AMD B650

Graphics: Integrated Graphics Processor: 1 x DisplayPort, supporting a maximum resolution of 3840x2160@144 Hz; * Support for DisplayPort 1.4 version and HDR.; 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz; * Support for HDMI 2.1 version and HDCP 2.3.; ** Support native HDMI 2.1 TMDS compatible ports.

Expansion Slots: CPU: 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x16 (PCIEX16); * For optimum performance, if only one PCI Express graphics card is to be installed, be sure to install it in the PCIEX16 slot.; Chipset: 2 x PCI Express x16 slots, supporting PCIe 3.0 and running at x1 (PCIEX1_1/2)

Storage: CPU: 2 x M.2 connectors (Socket 3, M key, type 25110/2280 support); M2A_CPU and M2B_CPU connectors support PCIe 4.0 x4/x2 SSD (PCB rev. 1.0/1.1); M2A_CPU connector supports PCIe 5.0* x4/x2 SSD, M2B_CPU connector supports PCIe 4.0 x4/x2 SSD (PCB rev. 1.2); * Actual support may vary by CPU.; Chipset: 1 x M.2 connector (Socket 3, M key, type 25110/2280 PCIe 4.0 x4/x2 SSD support) (M2C_SB); 4 x SATA 6Gb/s connectors; RAID 0, RAID 1, and RAID 10 support for NVMe SSD storage devices; RAID 0, RAID 1, and RAID 10 support for SATA storage devices

I/O: 1 x Q-Flash Plus button; 1 x DisplayPort; 1 x HDMI port; 1 x USB Type-C® port, with USB 3.2 Gen 2 support; 1 x USB 3.2 Gen 2 Type-A port (red); 3 x USB 3.2 Gen 1 ports; 3 x USB 2.0/1.1 ports; 1 x RJ-45 port; 3 x audio jacks

Connectors: 1 x 24-pin ATX main power connector; 1 x 8-pin

ATX 12V power connector; 1 x 4-pin ATX 12V power connector; 1 x CPU fan header; 1 x water cooling CPU fan header; 2 x system fan headers; 1 x system fan/water cooling pump header; 2 x addressable LED strip headers; 2 x RGB LED strip headers; 1 x CPU cooler LED strip/RGB LED strip header; 3 x M.2 Socket 3 connectors; 4 x SATA 6Gb/s connectors; 1 x front panel header; 1 x front panel audio header; 1 x USB Type-C header, with USB 3.2 Gen 2x2 support; 1 x USB 3.2 Gen 1 header; 2 x USB 2.0/1.1 headers; 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only); 1 x serial port header; 1 x reset button; 1 x reset jumper; 1 x Clear CMOS jumper
Audio: Realtek; Audio CODEC; High Definition Audio; 2/4/5.1/7.1-channel
LAN: Realtek; 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)
BIOS: 1 x 256 Mbit flash; Use of licensed AMI UEFI BIOS; PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Form Factor: ATX Form Factor; 30.5cm x 24.4cm
OS: Support for Windows 11 64-bit; Support for Windows 10 64-bit
Warranty: 36 Months

Цена : 421.09 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Сб 14 декември, 2024