

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки
GB H510M H V2 / LGA1200



Модел : GB H510M H V2 / LGA1200

GB H510M H V2 / LGA1200

CPU's supported: LGA1200 package: 11th Generation Intel® Core™ i9 processors / Intel® Core™ i7 processors / Intel® Core™ i5 processors; 10th Generation Intel® Core™ i9 processors / Intel® Core™ i7 processors / Intel® Core™ i5 processors / Intel® Core™ i3 processors/ Intel® Pentium® processors / Intel® Celeron® processors; L3 cache varies with CPU

Memory type: 11th Generation Intel® Core™ i9/i7/i5 processors: Support for DDR4

3200/3000/2933/2666/2400/2133 MHz memory modules;

10th Generation Intel® Core™ i9/i7 processors:

Support for DDR4 2933/2666/2400/2133 MHz memory

modules; 10th Generation Intel® Core™

i5/i3/Pentium®/Celeron® processors: Support for

DDR4 2666/2400/2133 MHz memory modules; 2 x DDR4

DIMM sockets supporting up to 64 GB (32 GB single DIMM

capacity) of system memory; Dual channel memory

architecture; Support for ECC Un-buffered DIMM 1Rx8/2Rx8

memory modules (operate in non-ECC mode); Support for

non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory

modules; Support for Extreme Memory Profile (XMP)

memory modules

Chipset: Intel® H470 Express Chipset

Graphics: Integrated Graphics Processor-Intel® HD

Graphics support: 1 x HDMI port, supporting a maximum

resolution of 4096x2160@30 Hz; * Support for HDMI 1.4

version and HDCP 2.3.; 1 x D-Sub port, supporting a

maximum resolution of 1920x1200@60 Hz; * The D-Sub port

is only available with the 10th Generation processors.

Expansion Slots: CPU: 1 x PCI Express x16 slot, supporting

PCIe 3.0 and running at x16; Chipset: 1 x PCI Express x1

slot, supporting PCIe 3.0 and running at x1

Storage: Chipset: 1 x M.2 connector (Socket 3, M key, type

2280 SATA and PCIe 3.0 x4/x2 SSD support); 4 x SATA 6Gb/s

connectors; RAID 0, RAID 1, RAID5, and RAID 10 support for

NVMe SSD storage devices; RAID 0, RAID 1, RAID5, and RAID

10 support for SATA storage devices

I/O: 1 x PS/2 keyboard/mouse port; 1 x D-Sub port; 1 x HDMI

port; 2 x USB 3.2 Gen 1 ports; 4 x USB 2.0/1.1 ports; 1 x

RJ-45 port; 3 x audio jacks

Connectors: 1 x 24-pin ATX main power connector; 1 x 8-pin ATX 12V power connector; 1 x CPU fan header; 1 x system fan header; 1 x RGB LED strip header; 1 x M.2 Socket 3 connector; 4 x SATA 6Gb/s connectors; 1 x front panel header; 1 x front panel audio header; 1 x USB 3.2 Gen 1 header; 1 x USB 2.0/1.1 header; 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only); 1 x serial port header; 1 x Clear CMOS jumper

Audio: Realtek®; Audio CODEC; High Definition Audio; 2/4/5.1/7.1-channel

LAN: Realtek®; GbE LAN chip (1 Gbps/100 Mbps/10 Mbps)

BIOS: 1 x 128 Mbit flash; Use of licensed AMI UEFI BIOS; PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Form Factor: Micro ATX Form Factor; 22.6cm x 18.5cm

OS: Support for Windows 11 64-bit; Support for Windows 10 64-bit

Warranty: 36 m

Цена : 144.00 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Сб 14 декември, 2024