

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

GB B450M DS3H WIFI /AM4



Модел : GB B450M DS3H WIFI /AM4

GB B450M DS3H WIFI /AM4

CPU's supported: AM4 Socket: Supports AMD Ryzen™ 5000 series / Ryzen™ 5000 G-Series/ 3rd Gen Ryzen™/ 2nd Gen Ryzen™/ 1st Gen Ryzen™/ 2nd Gen Ryzen™ with Radeon™ Vega Graphics/ 1st Gen Ryzen™ with Radeon™ Vega Graphics/ Athlon™ with Radeon™ Vega Graphics Processors

Memory type: 4 x DDR4 DIMM sockets supporting up to 128 GB of system memory; Dual channel memory architecture; Support for DDR4

3600(O.C.)/3466(O.C.)/2933/2667/2400/2133 MHz memory modules; Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode); Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules; Support for Extreme Memory Profile (XMP) memory modules

Chipset: AMD B450

Graphics: Integrated Graphics Processor: 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz(Note); * Support for HDMI 2.0 version and HDCP 2.2.(Note); Maximum shared memory of 16 GB

Expansion Slots: 1 x PCI Express x16 slot, running at x16 (PCIEX16)(Note); * For optimum performance, if only one PCI Express graphics card is to be installed, be sure to install it in the PCIEX16 slot.; (The PCIEX16 slot conforms to PCI Express 3.0 standard.); 1 x PCI Express x16 slot, running at x1 (PCIEX1_2); 1 x PCI Express x1 slot; (The PCIEX1_1 and PCIEX1_2 slots conform to PCI Express 2.0 standard.)

Storage: 1 x M.2 connector (Socket 3, M key, type 2242/2260/2280/22110 SATA and PCIe x4/x2* SSD support);

* Actual support may vary by CPU.; * Supports only M.2 SATA SSDs when using an AMD Athlon™-series/ 7th Gen. A-series or Athlon™ X4 APU.; 4 x SATA 6Gb/s connectors; Support for RAID 0, RAID 1, and RAID 10 I/O: 1 x PS/2 keyboard/mouse port; 1 x HDMI port; 4 x USB 3.1 Gen 1 ports; 4 x USB 2.0/1.1 ports; 2 x SMA antenna connectors (1T1R); 1 x RJ-45 port; 3 x audio jacks

Connectors: 1 x 24-pin ATX main power connector; 1 x 8-pin ATX 12V power connector; 1 x CPU fan header; 1 x system fan header; 1 x M.2 Socket 3 connector; 4 x SATA 6Gb/s connectors; 1 x front panel header; 1 x front panel audio

header; 1 x S/PDIF Out header; 1 x CPU cooler LED strip/RGB LED strip header; 1 x RGB LED strip header; 2 x addressable LED strip headers; 1 x USB 3.1 Gen 1 header; 2 x USB 2.0/1.1 headers; 1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only); 1 x serial port header; 1 x Clear CMOS jumper

Audio: Realtek® Audio CODEC; High Definition Audio; 2/4/5.1/7.1-channel; * You can change the functionality of an audio jack using the audio software. To configure 7.1-channel audio, access the audio software for audio settings.; Support for S/PDIF O

LAN: Realtek®; GbE LAN chip (1 Gbps/100 Mbps)

BIOS: 1 x 128 Mbit flash; Use of licensed AMI UEFI BIOS; PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Form Factor: Micro ATX Form Factor; 24.4cm x 21.5cm

OS: Support for Windows 10 64-bit; Support for Windows 7 64-bit; * To support Windows 7 64-bit, you must install an AMD Pinnacle Ridge & Summit Ridge CPU. * Please download the "Windows USB Installation Tool" from GIGABYTE's website and install it before installing Windows 7.

Other: AzureWave Wi-Fi AW-CB304NF (Realtek®; RTL8821CE); WIFI 802.11a, b, g, n, ac, supporting 2.4/5 GHz Dual-Band; BLUETOOTH 5.0; Support for 11ac wireless standard

Warranty: 36 Months

Цена : 176.72 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Вт 19 март, 2024