

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

## GB Z790 EAGLE AX /LGA1700



Модел : GB Z790 EAGLE AX /LGA1700

GB Z790 EAGLE AX /LGA1700

CPU's supported: LGA1700 socket: Support for the 14th, 13th, and 12th Generation Intel® Core™, Pentium® Gold and Celeron® Processors; L3 cache varies with CPU

Memory type: 14th and 13th Generation Intel® Core™; i9/i7 Processors: - Support for DDR5 7600(O.C.) /7400(O.C.) /7200(O.C.) /7000(O.C.) /6800(O.C.) /6600(O.C.) /6400(O.C.) /6200(O.C.) /6000(O.C.) /5800(O.C.) /5600 /5400 /5200/ 4800/4400 MT/s memory modules; 13th Generation Intel® Core™; i5/i3 and 12th Generation Intel® Core™, Pentium® Gold and Celeron® Processors: - Support for DDR5 4800/4400 MT/s memory modules; 4 x DDR5 DIMM sockets supporting up to 192 GB (48 GB single DIMM capacity) of system memory; Dual channel memory architecture; Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode); Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules; Support for Extreme Memory Profile (XMP) memory modules  
Chipset: Intel® Z790 Express Chipset

Graphics: Integrated Graphics Processor-Intel® HD Graphics support: - 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz; \* Support for HDMI 2.1 version and HDCP 2.3.; \*\* Support for native HDMI 2.1 TMDS compatible ports.; - 1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz; \* Support for DisplayPort 1.2 version and HDCP 2.3

Expansion Slots: CPU: - 1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16); \* The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot.; Chipset: - 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x4 (PCIEX4); - 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x1 (PCIEX1\_4); - 2 x PCI Express x1 slots, supporting PCIe 3.0 and running at x1 (PCIEX1\_2, PCIEX1\_3)

Storage: CPU: - 1 x M.2 connector (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2A\_CPU); Chipset: - 1 x M.2 connectors (Socket 3, M key, type 2280 PCIe 4.0 x4/x2 SSD support) (M2P\_SB); - 1 x M.2 connectors (Socket 3, M key, type 2280 SATA and PCIe 4.0 x4/x2 SSD

support) (M2M\_SB); - 4 x SATA 6Gb/s connectors; RAID 0, RAID 1, RAID 5, and RAID 10 support for NVMe SSD storage devices; RAID 0, RAID 1, RAID 5, and RAID 10 support for SATA storage devices

I/O: 1 x PS/2 keyboard/mouse port; 1 x USB Type-C&reg; port, with USB 3.2 Gen 2 support; 1 x USB 3.2 Gen 2 Type-A port (red); 4 x USB 3.2 Gen 1 ports; 2 x USB 2.0/1.1 ports; 2 x SMA antenna connectors (1T1R); 1 x HDMI port; 1 x DisplayPort; 1 x RJ-45 port; 3 x audio jacks

Connectors: 1 x 24-pin ATX main power connector; 2 x 8-pin ATX 12V power connectors; 1 x CPU fan header; 1 x CPU fan/water cooling pump header; 3 x system fan headers; 1 x system fan/water cooling pump header; 2 x addressable LED strip headers; 3 x M.2 Socket 3 connectors; 4 x SATA 6Gb/s connectors; 1 x front panel header; 1 x front panel audio header; 1 x S/PDIF Out header; 1 x USB Type-C&reg; header, with USB 3.2 Gen 1 support; 1 x USB 3.2 Gen 1 header; 2 x USB 2.0/1.1 headers; 2 x Thunderbolt&trade; add-in card connectors; 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI / GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only); 1 x reset button; 1 x Q-Flash Plus button; 1 x reset jumper; 1 x Clear CMOS jumper

Audio: Realtek&reg; Audio CODEC; High Definition Audio; 2/4/5.1/7.1-channel; \* You can change the functionality of an audio jack using the audio software. To configure 7.1-channel audio, access the audio software for audio settings. Support for S/PDIF Out

LAN: Realtek&reg; 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)

BIOS: 1 x 256 Mbit flash; Use of licensed AMI UEFI BIOS; PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Form Factor: ATX Form Factor; 30.5cm x 24.4cm

OS: Support for Windows 11 64-bit; Support for Windows 10 64-bit

Other: Intel&reg; Wi-Fi 6E AX211 (PCB rev. 1.0); - WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands; - BLUETOOTH 5.3; - Support for 11ax 160MHz wireless standard; Realtek&reg; Wi-Fi 6E RTL8852CE(PCB rev. 1.1); - WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands; - BLUETOOTH 5.3; - Support for 11ax 160MHz wireless standard

Warranty: 36 Months

Цена : 504.00 лв. с ДДС