

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

## GB X670 GAMING X AX V2/ AM5



Модел : GB X670 GAMING X AX V2/ AM5

GB X670 GAMING X AX V2/ AM5

CPU's supported: AMD Socket AM5, support for: AMD Ryzen™; 7000 / Ryzen™; 8000 Series Processors

Memory type: Support for DDR5 8000(OC)/ 7800(OC)/ 7600(OC)/ 7200(OC)/ 7000(OC)/ 6800(OC)/ 6600(OC)/ 6400(OC)/6200(OC)/6000(OC)/5600(OC)/5200/4800/4400 MT/s memory modules; 4 x DDR5 DIMM sockets supporting up to 192 GB (48 GB single DIMM capacity) of system memory; Dual channel memory architecture; Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules; Support for AMD Extended Profiles for Overclocking (AMD EXPO™;) and Extreme Memory Profile (XMP) memory modules

Chipset: AMD X670

Graphics: Integrated Graphics Processor: 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz; \* Support for HDMI 2.1 version and HDCP 2.3.; \*\* Support native HDMI 2.1 TMDs compatible ports.

Expansion Slots: 1 x PCI Express x16 slot (PCIEX16), integrated in the CPU: AMD Ryzen™; 7000 Series Processors support PCIe 4.0 x16 mode; AMD Ryzen™; 8000 Series-Phoenix 1 Processors support PCIe 4.0 x8 mode; AMD Ryzen™; 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4 mode; \* The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot.;

Chipset: 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x4 (PCIEX4); 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x2 (PCIEX2)  
Storage: 1 x M.2 connector (M2A\_CPU), integrated in the CPU, supporting Socket 3, M key, type 25110/2580 SSDs: AMD Ryzen™; 7000 Series Processors support PCIe 5.0 x4/x2 SSDs; AMD Ryzen™; 8000 Series-Phoenix 1/Phoenix 2 Processors support PCIe 4.0 x4/x2 SSDs; 1 x M.2 connector (M2B\_CPU), integrated in the CPU, supporting Socket 3, M key, type 22110/2280 SSDs: AMD Ryzen™; 7000 Series Processors support PCIe 4.0 x4/x2 SSDs; AMD Ryzen™; 8000 Series-Phoenix 1 Processors support PCIe 4.0 x4/x2 SSDs; AMD Ryzen™; 8000 Series-Phoenix 2 Processors support PCIe 4.0 x2 SSDs;

Chipset: 2 x M.2 connectors (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2C\_SB,

M2D\_SB); 4 x SATA 6Gb/s connectors; RAID 0, RAID 1, and RAID 10 support for NVMe SSD storage devices; RAID 0, RAID 1, and RAID 10 support for SATA storage devices  
I/O: 1 x Q-Flash Plus button; 2 x SMA antenna connectors (2T2R); 1 x HDMI port; 6 x USB 3.2 Gen 1 ports; 4 x USB 2.0/1.1 ports; 2 x USB 3.2 Gen 2 Type-A ports (red); 1 x USB Type-C&reg; port, with USB 3.2 Gen 2x2 support; 1 x RJ-45 port; 3 x audio jacks

Connectors: 1 x 24-pin ATX main power connector; 2 x 8-pin ATX 12V power connectors; 1 x CPU fan header; 1 x CPU fan/water cooling pump header; 3 x system fan headers; 3 x addressable RGB Gen2 LED strip headers; 1 x RGB LED strip header; 4 x SATA 6Gb/s connectors; 4 x M.2 Socket 3 connectors; 1 x front panel header; 1 x front panel audio header; 1 x USB Type-C&reg; header, with USB 3.2 Gen 2x2 support; 2 x USB 3.2 Gen 1 headers; 2 x USB 2.0/1.1 headers; 1 x THB\_U4 add-in card connector; 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/ GC-TPM2.0 SPI V2 module only); 1 x power button; 1 x reset button; 1 x Clear CMOS button; 1 x reset jumper; 1 x Clear CMOS jumper

Audio: Realtek&reg; Audio CODEC; High Definition Audio; 2/4/5.1/7.1-channel

LAN: Realtek&reg; 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)

BIOS: 1 x 256 Mbit flash; Use of licensed AMI UEFI BIOS; PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Form Factor: ATX Form Factor; 30.5cm x 24.4cm

OS: Support for Windows 11 64-bit; Support for Windows 10 64-bit

Other: Realtek&reg; Wi-Fi 6E RTL8852CE; WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands; BLUETOOTH 5.3; Support for 11ax 160MHz wireless standard

Warranty: 36 Months

Цена : 545.46 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пт 10 май, 2024