

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

GB X670E AORUS MASTER /REFURB



Модел : GB X670E AORUS MASTER /REFURB

GB X670E AORUS MASTER /REFURB

CPU's supported: AMD Socket AM5, support for : AMD Ryzen™; 7000 / Ryzen™; 8000 Series Processors
Memory type: Support for DDR5 8000(OC)/ 7800(OC)/ 7600(OC)/ 7200(OC)/ 7000(OC)/ 6800(OC)/ 6666(OC)/ 6600(OC)/ 6400(OC)/ 6200(OC)/ 6000(OC)/ 5600(OC)/ 5200/ 4800/ 4400 MT/s memory modules; 4 x DDR5 DIMM sockets supporting up to 192 GB (48 GB single DIMM capacity) of system memory; Dual channel memory architecture; Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules; Support for AMD Extended Profiles for Overclocking (AMD EXPO™;) and Extreme Memory Profile (XMP) memory module

Chipset: AMD X670

Graphics: Integrated Graphics Processor: 1 x DisplayPort, supporting a maximum resolution of 3840x2160@144 Hz; * Support for DisplayPort 1.4 version and HDR.; 1 x USB Type-C® port, supporting USB 3.2 Gen 2 and DisplayPort video outputs and a maximum resolution of 3840x2160@144 Hz; * Support for DisplayPort 1.4 version and HDR.; 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz; * Support for HDMI 2.1 version and HDCP 2.3.; ** Support native HDMI 2.1 TMDS compatible ports.

Expansion Slots:

Storage: 1 x M.2 connector (M2A_CPU), integrated in the CPU, supporting Socket 3, M key, type 25110/2580 SSDs: AMD Ryzen™; 7000 Series Processors support PCIe 5.0 x4/x2 SSD; AMD Ryzen™; 8000 Series-Phoenix 1 Processors support PCIe 4.0 x4/x2 SSD; AMD Ryzen™; 8000 Series-Phoenix 2 Processors support PCIe 4.0 x2 SSD; 1 x M.2 connector (M2B_CPU), integrated in the CPU, supporting Socket 3, M key, type 22110/2280 SSDs: AMD Ryzen™; 7000 Series Processors support PCIe 5.0 x4/x2 SSD; AMD Ryzen™; 8000 Series-Phoenix 1 Processors support PCIe 4.0 x4/x2 SSD; AMD Ryzen™; 8000 Series-Phoenix 2 Processors support PCIe 4.0 x4/x2 SSD; 2 x M.2 connectors (M2C_SB, M2D_SB), integrated in the Chipset, supporting Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD; 6 x SATA 6Gb/s connectors; * The PCIEX2 slot shares bandwidth with the SATA3 4/5 connectors. The SATA3 4/5 connectors will become unavailable when a

device is installed in the PCIEX2 slot.; RAID 0, RAID 1, and RAID 10 support for NVMe SSD storage devices; RAID 0, RAID 1, and RAID 1

I/O: 1 x Q-Flash Plus button; 2 x SMA antenna connectors (2T2R); 1 x DisplayPort; 1 x HDMI port; 1 x USB Type-C® port (DisplayPort), with USB 3.2 Gen 2 support; 1 x USB Type-C® port, with USB 3.2 Gen 2x2 support; 4 x USB 3.2 Gen 2 Type-A ports (red); 4 x USB 3.2 Gen 1 ports; 2 x USB 2.0/1.1 ports; 1 x RJ-45 port; 1 x optical S/PDIF Out connector; 2 x audio jacks

Connectors: 1 x 24-pin ATX main power connector; 2 x 8-pin ATX 12V power connectors; 1 x CPU fan header; 1 x water cooling CPU fan header; 4 x system fan headers; 4 x system fan/water cooling pump headers; 2 x addressable LED strip headers; 2 x RGB LED strip headers; 1 x CPU cooler LED strip/RGB LED strip header; 4 x M.2 Socket 3 connectors; 6 x SATA 6Gb/s connectors; 1 x front panel header; 1 x front panel audio header; 1 x USB Type-C® header, with USB 3.2 Gen 2x2 support; 2 x USB 3.2 Gen 1 headers; 2 x USB 2.0/1.1 headers; 1 x noise detection header; 1 x THB_U4 add-in card connector; 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only); 1 x power button; 1 x reset button; 1 x reset jumper; 1 x Clear CMOS jumper; 2 x temperature sensor headers; Voltage Measurement Points

Audio: Realtek®; ALC1220-VB CODEC; * The back panel line out jack supports DSD audio.; Support for DTS:X®; Ultra; High Definition Audio; 2/4/5.1/7.1-channel output; * You can change the functionality of an audio jack using the audio software. To configure; 7.1-channel audio, access the audio software for audio settings.; Support for S/PDIF Out LAN: Intel®; 2.5GbE LAN chip (2.5 Gbps/1 Gbps/100 Mbps)

BIOS: 1 x 256 Mbit flash; Use of licensed AMI UEFI BIOS; PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Form Factor: E-ATX Form Factor; 30.5cm x 26.9cm

OS: Support for Windows 11 64-bit; Support for Windows 10 64-bit

Other: Intel®; Wi-Fi 6E AX210 (PCB rev. 1.0); WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands; BLUETOOTH 5.3; Support for 11ax 160MHz wireless standard and up to 2.4 Gbps data ; AMD Wi-Fi 6E RZ616 (MT7922A22M) (PCB rev. 1.1); WIFI a, b, g, n, ac, ax, supporting 2.4/5/6 GHz carrier frequency bands; BLUETOOTH 5.2; Support for 11ax 160MHz wireless standard and up to 2.4 Gbps data rate

Warranty: 24 Months



Цена : 569.12 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пт 10 май, 2024

November 23, 2024, 4:28 a.m.