

КОМПЮТРИ И СЪРВЪРИ > Сървъри

Dell PowerEdge T150, Chassis 4x 3.5", Intel Xeon E-2314 (8M Cache, 2.8GHz), 16GB (1x16GB) 3200MHz UDIMM ECC, 1x 2TB SATA (7.2k rpm) 3.5" Entry, On-Board Broadcom 5720 Dual Port 1Gb LOM, PERC H355 Adapter FH (Raid 0,1,10), iDRAC9 Basic 15G, 3Y Basic Onsite



Модел : EMEA_PET150SPL4

Dell PowerEdge T150, Chassis 4x 3.5", Intel Xeon E-2314 (8M Cache, 2.8GHz), 16GB (1x16GB) 3200MHz UDIMM ECC, 1x 2TB SATA (7.2k rpm) 3.5" Entry, On-Board Broadcom 5720 Dual Port 1Gb LOM, PERC H355 Adapter FH (Raid 0,1,10), iDRAC9 Basic 15G, 3Y Basic Onsite

Серия: PowerEdge T150

Процесор: Intel Xeon E-2314 2.80 GHz, 4-core, 8MB cache

Памет, GB: 6GB (1x16GB) 3200MHz UDIMM ECC

Памет, слотове: 4x DDR4 DIMM slots, supports UDIMM 128 GB max, speeds up to 3200 MT/s; Supports unregistered ECC DDR4 DIMMs only

Твърд диск, GB: 1x 2TB SATA (7.2k rpm) 3.5" Entry

Дисков контролер: PERC H355 Adapter FH (Raid 0,1,10)

Брой поддържани дискове: 4x 3.5-inch cabled SAS/SATA (HDD/SSDs) max 30.72 TB

Оптично устройство: -

Мрежа: On-Board Broadcom 5720 Dual Port 1Gb LOM

Разширителен слот: 2x PCIe Gen4 slots and 2x PCIe Gen3 slots

Интерфейс: Front: 1x iDRAC Direct (Micro-AB USB) port, 1x USB 3.0; Rear: 5x USB 2.0, 1x iDRAC ethernet port, 1x USB 3.0, 1x Serial port, 1x VGA; Internal: 1x USB 3.0 (optional)

Порт за отдалечено управление: yes

Захранване: European Power Cord 220V

Съвместими операционни системи: Canonical Ubuntu Server LTS, Citrix Hypervisor, Microsoft Windows Server with Hyper-V, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi (support only from Dec'21)

Софтуер за управление: iDRAC9 Basic 15G

Форм-фактор: 4U Tower

Тип на шасито: Cabled

Други: Trusted Platform Module 2.0 V3

Цена : 3203.93 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пт 10 май, 2024