

ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Декодери

HikVision 32-ch 1U K Series AcuSense 4K NVR, Up to 32-ch IP camera inputs, Up to 12 MP (12x1080p/2x12MP), H.265+, 2 SATA HDD up to 10TB each, 2 USB, Video input: HDMI 4K, VGA 1080p, 12Vdc, 3.3 A



Модел : DS-7632NXI-K2

HikVision 32-ch 1U K Series AcuSense 4K NVR, Up to 32-ch IP camera inputs, Up to 12 MP (12x1080p/2x12MP), H.265+, 2 SATA HDD up to 10TB each, 2 USB, Video input: HDMI 4K, VGA 1080p, 12Vdc, 3.3 A

Тип: IP Recorder

Брой канали: Up to 32-ch IP camera inputs

HDMI: 1-ch, 4K (3840 x 2160)/30 Hz, 2K (2560 x 1440)/60 Hz, 1920 x 1080/60 Hz, 1600 x 1200/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz, 1024 x 768/60 Hz

VGA: 1-ch, 1920 x 1080/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz

Видео изходен режим: HDMI/VGA independent output

Капацитет: Incoming Bandwidth: 256 Mbps; Outgoing Bandwidth: 160 Mbps

Аудио: 1-ch, RCA (2.0 Vp-p, 1 KO, using the audio input); Two-Way Audio 1-ch, RCA (Linear, 1 KO)

Видео компресия: H.265/H.265+/H.264+/H.264

Аудио компресия: G.711ulaw/G.711alaw/G.722/G.726/AAC

Резолюция на запис: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Дистанционна връзка: Up to 128 Remote Connections

Мрежови протоколи: TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS

Мрежов интерфейс: 1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface; AUDIO IN and AUDIO OUT

Спомагателен интерфейс: 2x SATA interface (Capacity: Up to 10 TB capacity for each HDD); Front panel: 1 Ч USB 2.0; Rear panel: 1 Ч USB 2.0

Захранване: 12 VDC, 3.3 A; Consumption: $\leq 15 W$ (without HDD)

Power Over Ethernet (PoE): -

Размери (Ш, Д, В), mm: 385 x 315 x 52 mm

Тегло, g: $\leq 1 kg$

Цена : 626.63 лв. с ДДС



Наличност: Този продукт е бил добавен в нашия каталог на Пн 01 юли, 2024

November 22, 2024, 2:17