

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Aruba IOn 1930 48G 4SFP+ 370W Sw



Модел : JL686A

Aruba IOn 1930 48G 4SFP+ 370W Sw

Суич, тип: Fixed Port, Smart Managed

Общ брой портове: 52

Основни портове, тип: 48x10/100/1000Base-T

Power Over Ethernet (PoE): IEEE 802.3 Type 10BASE-T,

IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type

1000BASE-T; 370 W Class 4 PoE

Uplink портове: 4 SFP/SFP+

Свободни (10GB) слотове: No

Управление: Aruba Instant On Portal; Web browser; SNMP

Manager; Management VLAN ID

Stackable: No

Fans: Variable speed fans

Захранване: AC voltage: 100 - 127/200 - 240 VAC;

Maximum power rating: 460 W, Current: 5/2.5 A; Frequency:

50/60 Hz

Routing: Layer 3 IPv4 static routing (Supports manual

routing configuration of up to 32 static routes)

Памет (Flash, RAM): 512 MB SDRAM, 256 MB flash; packet

buffer: 1.5 MB

Капацитет за маршрутизиране/превключване, Gbps:

176 Gbps

Пропускателна способност, Mpps: 130.95 Mpps

MAC адреси: 16000 MAC address table size

VLAN (брой, стандарти): IEEE 802.1p/Q VLAN tagging;

IEEE 802.1Q VLAN support - Support for up to 256 VLANs

with a VLAN ID range of 2-4093; RADIUS assigned VLAN,

dynamic VLAN creation, guest VLAN or into an

unauthenticated VLAN; Auto-voice VLAN.

QoS: Traffic prioritization - time-sensitive packets (like VoIP

and video) with priority over other traffic based on DSCP or

IEEE 802.1p classification. IEEE 802.1p/DSCP priority to

queue mapping. Supports SP or WRR. Advanced classifier

based QoS.

L2 мрежови стандарти: 802.3 10 BASE-T, 802.3u

100BASE-TX, 802.3ab 1000BASE-T, 802.3z 1000BASE-X ,

802.2af/at PoE, 802.3x, 802.1Q VLANs, 802.1p Priority,

802.3ad LACP, 802.1X, 802.3az

L3 мрежови стандарти: 802.1D (Spanning Tree Protocol),

802.1W: Rapid Spanning Tree Protocol, 802.1S: Multiple

Spanning Tree Protocol; 802.1AB Link Layer Discovery

Protocol

IPv6 functionality: IPv6 Host mode - Enables switches to be managed and deployed at the IPv6 network's edge

Сигурност: TPM, IEEE 802.1Q VLAN support; IEEE 802.1X access control; Automatic denial-of-service protection; Packet storm protection; RADIUS; RADIUS accounting; Management VLAN ID; Link Flap prevention

Размери (Ш, Д, В), mm: 442.5 x 322.6 x 44

Опция за монтаж: Rackmount (1U)

Цена : 1609.96 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пт 19 юли, 2024