

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Aruba IOn 1930 24G 4SFP+ 195W Sw



Модел : JL683B

Aruba IOn 1930 24G 4SFP+ 195W Sw

Суич, тип: Fixed Port, Smart Managed

Общ брой портове: 28

Основни портове, тип: 24x10/100/1000Base-T

Power Over Ethernet (PoE): IEEE 802.3 Type 10BASE-T,

IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type

1000BASE-T; 195 W Class 4 PoE

Uplink портове: 4 SFP/SFP+

Свободни (10GB) слотове: No

Управление: Aruba Instant On Cloud; Web browser; SNMP
Manager

Stackable: No

Fans: Variable speed fans

Захранване: AC voltage: 100 - 127/200 - 240 VAC;

Maximum power rating: 248.7 W, Current: 2.8 A/1.4 A;

Frequency: 50/60 Hz

Routing: Layer 3 IPv4 static routing (Supports manual
routing configuration of up to 32 static routes)

Памет (Flash, RAM): 512 MB SDRAM, 256 MB flash; packet
buffer: 1.5 MB

Капацитет за маршрутизиране/превключване, Gbps:
128 Gbps

Пропускателна способност, Mpps: 95.23 Mpps

MAC адреси: 16000 MAC address table size

VLAN (брой, стандарти): IEEE 802.1p/Q VLAN tagging;
IEEE 802.1Q VLAN support - Support for up to 256 VLANs
with a VLAN ID range of 2-4093; RADIUS assigned VLAN,
dynamic VLAN creation, guest VLAN or into an
unauthenticated VLAN; Auto-voice VLAN.

QoS: Traffic prioritization - time-sensitive packets (like VoIP
and video) with priority over other traffic based on DSCP or
IEEE 802.1p classification. IEEE 802.1p/DSCP priority to
queue mapping. Supports SP or WRR. Advanced classifier
based QoS.

L2 мрежови стандарти: 802.3 10 BASE-T, 802.3u
100BASE-TX, 802.3ab 1000BASE-T, 802.3z 1000BASE-X ,
802.2af/at PoE, 802.3x, 802.1Q VLANs, 802.1p Priority,
802.3ad LACP, 802.1X, 802.3az

L3 мрежови стандарти: 802.1D (Spanning Tree Protocol),
802.1W: Rapid Spanning Tree Protocol, 802.1S: Multiple
Spanning Tree Protocol; 802.1AB Link Layer Discovery
Protocol

IPv6 functionality: IPv6 Host mode - Enables switches to be managed and deployed at the IPv6 network's edge

Сигурност: TPM, IEEE 802.1Q VLAN support; IEEE 802.1X access control; Automatic denial-of-service protection; Packet storm protection; RADIUS; RADIUS accounting; Management VLAN ID; Link Flap prevention

Размери (Ш, Д, В), mm: 442.5 x 264.7 x 44

Опция за монтаж: Desktop/Rackmount

Цена : 845.71 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 24 юли, 2024