

UPS И ЗАЩИТИ > On Line UPS

TUNCMATIK NEWTECH PRO II X9 3K



Модел : TUNCMATIK NT PRO2 ONLINE 3KVA

TUNCMATIK NEWTECH PRO II X9 3K

Manufacturer: TUNCMATIK

Mnfr Part #: TSK5309

Model: Newtech Pro II 3 kVA

Capacity: 3 kVA

Type: On-Line

Input: Nominal voltage:200/208/220/230 / 240VAC; Voltage range Low voltage transfer:100% -80% load 160 VAC \pm 5%, 80% -70% load 140 VAC \pm 5%, 70-60% load 120 VAC \pm 5%, 60% -0% load 110 VAC \pm 5%, (< 35 [deg.] C); Voltage range Low voltage correction:100% -80% load 175 VAC \pm 5%, 80% -70% load 155 VAC \pm 5%, 70-60% load 135 VAC \pm 5%, 60% -0% load 125 VAC \pm 5%, (< 35 [deg.] C); Voltage range High voltage transfer:300 VAC \pm 5%; Voltage range High voltage correction:290 VAC \pm 5%; Frequency range:40 Hz to 70 Hz; Power factor:At 100% load 0.990 (Nominal input voltage); Bypass voltage range:Bypass high voltage point 200/208/220/230/240 VAC output models; Bypass voltage range:Bypass low voltage point 200/208/220/230/240 VAC output models; Phase:One phase + Soil.

Output:

Alarms: Battery Mode, Low Battery, Overload, Fault

Display: LCD Panel:UPS status, Load level, Battery level,

Input / Output voltage, Discharge counter, Error status

Battery: Type of battery: 12V9AH; Number of battery: 6;

Charge time: Depends on external battery capacity; Charge

voltage: 82.1 VDC \pm %1; Charge current: 1A.

Environment: Operating temperature:0-40 ° C;

Moisture:20-90% relative humidity (non-condensing); Noise level:

Цена : 798.54 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 24 октомври, 2024