

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 28-Port Gigabit Stackable SmartPro PoE Switch including 2 SFP ports and 2 x 10G SFP+ ports



Модел : DGS-1510-28P

D-Link 28-Port Gigabit Stackable SmartPro PoE Switch including 2 SFP ports and 2 x 10G SFP+ ports

Суич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 24x10/100/1000Base-T

Power Over Ethernet (PoE): IEEE 802.3af and IEEE 802.3at

PoE Standard; PoE Capable Ports (Ports 1 to 24: Up to 30 W);

PoE Power Budget: Max. 193 W

Uplink портове: 2xSFP, 2x10GE SFP

Свободни (10GB) слотове: No

Управление: CLI, Telnet Server, TFTP Client, IPv6 Neighbor Discovery, Configurable MDI/MDIX, SNMP (Supports v1, v2c, v3), SNMP Trap, System Log, DHCP Client, D-Link Network Assistant support, SNTp, ICMPv6, IPv4/v6 Dual Stack, DHCP Auto Configuration, RMON v1

Stackable: Virtual Stacking Support: D-Link Single IP

Management, Up to 32 devices per virtual stack, Up to 20G

stacking bandwidth; Physical Stacking: Supports Duplex

Chain/Ring topology, Up to 40G stacking bandwidth full

duplex, Up to 6 units per stack

Fans: 2 Smart Fans

Захранване: AC Input: 100 to 240 VAC 50/60 Hz internal

universal power supply; Maximum Power Consumption:

238.7 W (PoE on), 29 W (PoE off)

Routing: Layer 3 Lite

Памет (Flash, RAM): -

Капацитет за маршрутизиране/превключване, Gbps: 92

Gbps

Пропускателна способност, Mpps: 68.45 Mpps

MAC адреси: 16000 MAC address table size

VLAN (брой, стандарти): 802.1Q Tagged VLAN, 4K VLAN

Groups, Configurable VID: 0~4094, Asymmetric VLAN, Auto

Voice VLAN, Auto Surveillance VLAN

QoS: 802.1p Quality of Service, Queue Handling (Strict,

Weighted Round Robin (WRR)), 8 queues per port,

Bandwidth Control - Port-based (Ingress/Egress, min.

granularity for 10/100/1000Base-T ports is 64 Kb/s)

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE

802.3ab, 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3x,

Spanning Tree Protocol: IEEE 802.1D STP, IEEE 802.1w RSTP,

IEEE 802.1s MSTP; IEEE 802.3ad Link Aggregation, IEEE

802.3az Energy Efficient Ethernet

L3 мрежови стандарти: Default Routing, Static Routing: 64

IPv4 Static Route Entries, 32 IPv6 Static Route Entries

IPv6 functionality: IPv6 Neighbour Discovery (ND), IPv6 flow label, IPv6 Management Support, IPv6 Ready Logo Phase 2

Сигурност: Port Security, Broadcast/Multicast/Unicast Storm Control, Dynamic ARP Inspection, Static MAC, D-Link

Safeguard Engine, DHCP Server Screening, ARP Spoofing

Prevention, SSH, SSL, Traffic Segmentation, IP-MAC-Port

Binding, DoS Attack Prevention, ACLs

Размери (Ш, Д, В), mm: 440 x 250 x 44

Опция за монтаж: Rackmount

Други: Green Technology: IEEE 802.3az Energy Efficient Ethernet, D-Link Green 3.0 power-saving features (Power

Saving by: Link Status, LED or Port Shutoff, System

Hibernation mode, Time-based PoE (PoE model only))

Цена : 1585.54 лв. с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пн 24 юни, 2024