

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

## D-Link 20-Port 10GBASE-T/SFP+ and 10GBASE-T/SFP+ Combo Port



Модел : DXS-3400-24TC

D-Link 20-Port 10GBASE-T/SFP+ and 10GBASE-T/SFP+ Combo Port

Суич, тип: Fixed Port

Общ брой портове: 24

Основни портове, тип: 20x10GBase-T

Power Over Ethernet (PoE): No

Uplink портове: 4 dual personality

Свободни (10GB) слотове: No

Управление: Web-based GUI, CLI, Telnet Server/Client, TFTP

Client, FTP Client, Traffic Monitoring, SNMP (Supports

v1/v2c/v3), SNMP Trap, System Log, CPU Monitoring,

RMONv1, RMONv2, Trusted Host, Debug command, sFlow,

Switch Resource Management (SRM), LLDP &

LLDP-MED

Stackable: Physical Stacking: Up to 80G stacking bandwidth,

Up to 4 switches in a stack, Ring/chain topology support;

Virtual Stacking/Clustering of up to 32 units: Supports D-Link

Single IP Management

Fans: Three hot-swappable fan trays provide N+1 cooling

redundancy

Захранване: Two AC/DC hot-swappable power modules for

1+1 power redundancy and load sharing

Routing: Layer 3 RIP

Памет (Flash, RAM): -

Капацитет за маршрутизиране/превключване, Gbps: 480

Gbps

Пропускателна способност, Mpps: 357.14 Mpps

MAC адреси: 48000 MAC address table size

VLAN (брой, стандарти): 802.1Q, 802.1v, Double VLAN

(Q-in-Q), Selective Q-in-Q, Port/MAC/Subnet-based VLAN,

Private VLAN, VLAN Group (Max. 4K static VLAN groups,

Max. 4094 VIDs), ISM VLAN (Multicast VLAN), GVRP (Up to

4094 dynamic VLANs), Voice VLAN, Auto Surveillance VLAN

QoS: 802.1p Quality of Service (QoS), 8 queues per port,

Queue handling (Strict, Weighted Round Robin (WRR), Strict

+ WRR, Deficit Round Robin (DRR), Weighted Deficit Round

Robin (WDRR)), Bandwidth Control, Congestion Control

L2 мрежови стандарти: IEEE 802.3u, IEEE 802.1D, IEEE

802.1w, IEEE 802.1s, IEEE 802.3x, IEEE 802.1X, IEEE 802.1Q,

IEEE 802.1v, IEEE 802.1AX, IEEE 802.1p, IEEE 802.1Qbb,

IEEE 802.1Qaz, IEEE 802.1Qau, IEEE 802.3ah, IEEE 802.1ag

L3 мрежови стандарти: Static Routing: Max. 256 IPv4

entries, Max. 128 IPv6 entries, Supports route redistribution, Supports secondary route; Default Routing; Policy-based Route (PBR); Bidirectional Forwarding Detection (BFD); RIP (RIP v1/v2, RIPng); Route Redistribution  
IPv6 functionality: IPv6 Neighbor Discovery (ND), IPv6 Tunneling - Static, ISATAP, GRE, 6to4  
Сигурност: Port Security, Broadcast/Multicast/Unicast Storm Control, D-Link Safeguard Engine, DHCP Server Screening, IP-MAC-Port Binding (IMPB), Dynamic ARP Inspection, IP Source Guard, DHCP Snooping, DHCPv6 Guard, BPDU Attack Protection, DOS Attack Prevention, SSH  
Размери (Ш, Д, В), mm: 441 x 380 x 44  
Опция за монтаж: Rackmount  
Други: 10/100/1000BASE-T RJ-45 Ethernet for out-of-band IP management, RJ45 and Mini USB console ports for out-of-band CLI management, 1 USB Port

Цена : 16875.88 лв. с ДДС

*Наличност: Този продукт е бил добавен в нашия каталог на Пн 24 юни, 2024*